	,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,
1-R.J. STARRAK-TULSA 1-BH	Form Approved. Copy to ST
Porm 9-331 1-A.B. CARY-MIDLAN 1-HAO, ENGR. N. M.	O C Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE 77 4 2 6 8 8 8 8
DEPARTMENT OF THE INTERIOR	LC-029420-A3355 - 335
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME: 357 Skelly Unit 1876 3 257
(Do not use this form for proposals to drill or to deepen or plug back to veiffeen breservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME SER
1 oil gas	OF TARREST OF THE PARTY OF THE
well Cx well other AUC 2.9 1978	9. WELL NO.
2. NAME OF OPERATOR	152 g ( ) g ( ) g ( ) g ( )
Getty Oil Company 🗸	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR  D. C. C.  P. O. Boy 720 Hobbs New Mark Street Of the Control of the Cont	Fren 7-Rivers
1. U. DOX 750, NODDS, New Mexico 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA CERCATE MATERIAL STATES
below.) AT SURFACE: UNIT LTR L, 1830' FSL & 660' FWL	SEC. 15, T-17-S, R-31-E 3-5
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH   13. STATE
AT TOTAL DEPTH:	14 ADI NO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 12.00 E 3.00.2
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	3863' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING [	change on Form 9-330.) 👙 🐧 🚊
MULTIPLE COMPLETE	
ABANDON*	그 대접임 등 전 배경 <b>3 전</b> 된 당시 : : : : : : : : : : : : : : : : : :
(other)	atructions
17 DESCRIPE PROPOSED OR COMPLETED OPERATIONS (OLD-1)	
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d</li> </ol>	irectionally drilled give subsurface locations and
measured and true vertical depths for all markers and zones pertinen	it to this work.)*
La Rue Drilling Co. spudded 11" hole at 1:30 p.m. on 7/22/78. Drilled 11"	
hole to 570' Set 8 5/8" 23# K-55 casing 6 56	.m. on //22//8. Orilled II
hole to 570'. Set 8 5/8" 23# K-55 casing 6 569', and B.J. cemented with 150 sxs. Lite Wate, 1/4# Flo-cel and 125 sxs. Class "C" cement with 2% CaCl.	
Plug down @ 5:00 a.m. 20 sxs. cement circulated. Tested casing with 1000#	
for 30 minutes with no drop in pressure.	ca. redeca casting with roots
•	
	\$ <b>4.2</b> \$ 18 \$
	46 <b>45</b> 134 6 325 6
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
AMELA II ( Character Area Synt	8/25/78 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3
signed // Dale R. Crockett	DATE
(This space for Federal or State office use)	
APPROVED BY JOE OF J. LASA ACTING DISTRICT E	NGINEERTE AUG 2 8 1978
CONDITIONS OF APPROVAL, IF ANY:	1 4 2 2 3 4 5 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
arnothing	
	유리는 사람들은 사람들은 사람들은 사람들은 사람들은 사람들이 되었다.
	A. 特勒 一节 一番毒蟲