

1-R.J. STARRAK-TULSA 1-BH
1-A.B. CARY-MITCHELL AND 1-HAO, ENGR.
UNITED STATES 1-ECF, FOREMAN

Form Approved.
Budget Bureau No. 42-R1424

Copy to 87

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ AUG 29 1978

2. NAME OF OPERATOR
Getty Oil Company ☒ O. C. C.

3. ADDRESS OF OPERATOR
P. O. Box 730, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: UNIT LTR L, 1830' FSL & 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to 2550' and set 65 jts. (2540') 5 1/2" OD 14# and 15.5# K-55 R-3 "A" casing @ 2549' on 7/26/78. B.J. cemented with 355 sxs Lite Wate, 10# salt, 1/4# Flo-cel, and 200 sxs. Class "C" cement with 2% CaCl. Plug down at 11:30 a.m. Circulated 45 sxs. Tested casing with 1500# for 30 minutes with no drop in pressure.

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO
AUG 28 1978

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Date R. Crockett TITLE Area Supt. DATE 8/25/78

(This space for Federal or State office use)
APPROVED BY Joe L. Lara TITLE ACTING DISTRICT ENGINEER DATE AUG 28 1978
CONDITIONS OF APPROVAL, IF ANY: