UNITED TES 1-ECF, Foreman DEPARTMENT OF THE INTERIOR	5. LEAS		<u> </u>	et Bure ್ತ	au No. 42-R142	4
GEOLOGICAL SURVEY		02942 Dian, a		OR TI	RIBENAME	_
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	Ske	lly t	<u> Mit</u>		RECE	ĪVED
1. oil gas uvell other	FARM		ASE NAM	/E 3	AUG 1 8	1978
2. NAME OF OPERATOR Getty Oil Company	153		<u> </u>		G.C.	C.
3. ADDRESS OF OPERATOR	10. FIELD		ildcat i Livers	IAME	ARTERIA,	UFFICE
D 0 D 700				BIK A	ND SURVEY O	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec.	. 15,	T-17-	·S, R	-31-E	r.
AT SURFACE: UNIT LETTER G, 2080' FWI & 1880' FET AT TOP PROD. INTERVAL:	12. COUN	NTY OR	PARISH	13.	STATE	
AT TOTAL DEPTH:	Eddy	У	<u> </u>		Mexico	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API N	10.		<u>.</u>	15 G	
REPORT, OR OTHER DATA	15. ELEV	ATIONS	S (SHOW	DF, H	(DB, AND WD))
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF [X]						-
FRACTURE TREAT			o and the second	ੋ ਵਵ	1 3 6 4 5 5 6 4 5 5 7 1	
SHOOT OR ACIDIZE				Ē		
PULL OR ALTER CASING	(NOTE: R	eport res	sults of mi	iltiple c	ompletion or zon	1 e
MULTIPLE COMPLETE	Ci	nange or	n Form 9-	330.) <u>:</u> <u>5</u>		
CHANGE ZONES		•				
(other)		11		3/10/		or or of oth
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is directly measured and true vertical deaths for all markets and true vertical deaths for all markets and true vertical deaths for all markets.	all pertine	nt deta	cg 35 ails, and	ੁੱ give ੀ	erunent date:	Š.
measured and true vertical depths for all markers and zones pertinent	o this wor	rk.)*	give sub	surrace	locations an	९ । संस्थ
In Pro amedded 1111 hala Q (20 m 0 0 7	0 1			(i, Σ, 139n	· 表示	العالم والشي
La Rue spudded 11" hole @ 6:30 p.m. 8-2-7 Ran 8 5/8" 23# 8rd ST&C and set @ 631'. B.J. c Poz, 4% Ge1, 10# salt, 1/4# Cello Flakes sack	emented	l wit	h 150	SXS.	50/50	
2% CaCl. Cement circulated. Test surface cas	ing to	1000	# for	30 m	in. 0:K.	
	Ü	á.	10년 년 12년 - 12년	3		
		3 .		11:23	원 (1년 년 1년 (1년 년 1년 (1년 년 년 년 년 년 년 년 년 년 년 년 년 년 년 년 년 년	
		j.		5	3 5 5 3 3 5 8 ±	
				5 A		
				불류		
		17				
Subsurface Safety Valve: Manu. and Type			Set	@	V 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	t.
18. I hereby certify that the foregoing is true and correct			John (
SIGNED Daie K. Crockett TITLE Area Supt.	DATE		August	14,	1978	_
APPROVED BY ACTING DISTRICT FACTOR OF APPROVAL LEADS AND TITLE IN C. DISTRICT FACTOR OF APPROVAL LEADS AND THE ARCHITECTURE OF ARCHI			Δ	UG 1	7 1978	•
CONDITIONS OF APPROVAL, IF ANY:	HNEERAT	E		- 	- 1040 <u>-</u> -3 - 5 - 5	-
		# 			() () () () () () () () () ()	