1-ARTESIA 1-FD, ENGR. 1-BH, FIELD CLERK N. M. Copy to SF
1-R.J. STARRAK-TUL CA 1-ECF, FOREMAN
1-A.B. CARY-MIDLAND 1-FILE

Form 9-330 (Rev. 5-63)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE* (See other instructions on reverse side)

Form approved. Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

RECEIVED
OCT 30 1978
O. C. C.
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.: LC-029420-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME: -
7. UNIT AGREEMENT NAME: Skelly Unit
8. FARM OR LEASE NAME: -
9. WELL NO.: 153
10. FIELD AND POOL, OR WILDCAT: Fren 7-Rivers
11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA: Sec. 15, T-17-S, R-31-E

1a. TYPE OF WELL: OIL WELL [X] GAS WELL [ ] DRY [ ] Other
b. TYPE OF COMPLETION: NEW WELL [X] WORK OVER [ ] DEEP-EN [ ] PLUG BACK [ ] DIFF. RESVR. [ ] Other
2. NAME OF OPERATOR: Getty Oil Company
3. ADDRESS OF OPERATOR: P. O. Box 730, Hobbs, New Mexico 88240
4. LOCATION OF WELL (*Report location clearly and in accordance with any State requirements*)*
At surface: Unit Ltr. G, 2080' ~~FWL~~ FNL & 1880' FEL
At top prod. interval reported below
At total depth

14. PERMIT NO. | DATE ISSUED
12. COUNTY OR PARISH: Eddy | 13. STATE: NM

15. DATE SPUDDED	16. DATE T.D. REACHED	17. DATE COMPL. (*Ready to prod.*)	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*	19. ELEV. CASINGHEAD
8-2-78	8-5-78	9-6-78	3881' GL	-

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
2629'	2586'	-	→	0-2629'	-

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*: 2331-2454 = 21 (.32") Holes - 7 - Rivers
25. WAS DIRECTIONAL SURVEY MADE: Yes
26. TYPE ELECTRIC AND OTHER LOGS RUN: Dresser Atlas: PFC Log, CN-FD, BHC-Sonic, DLL & MLL Logs.
27. WAS WELL CORED: No

28. CASING RECORD (*Report all strings set in well*)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8	23#	631	11	275 sx	25 sx cmt. circ.
5 1/2	14 & 15#	2629	7 7/8	650 sx	50 sx cmt. circ.

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 3/8	2465	-

31. PERFORATION RECORD (*Interval, size and number*)
2331,34,39,41,45,55,60,69,70,74,76,84,90, 2407,22,28,33,38,47,49, & 54 = 21 (.32") holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
2331-2454'	3150 gals. 15% NE acid & 42 ball sealers, 41,000# gel 2% KCL water, 48,300# 20/40 sand, & 11 ball sealers in 2 stages.

33.* PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (*Flowing, gas lift, pumping—size and type of pump*)	WELL STATUS (*Producing or shut-in*)
9-7-78	Pump 2" x 1 1/2" x 12'	Producing

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD →	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
10-19-78	24	-	→	1	3	12	3000

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
-	-	→	-	-	-	37.6

34. DISPOSITION OF GAS (*Sold, used for fuel, vented, etc.*): Sold
TEST WITNESSED BY:
35. LIST OF ATTACHMENTS: Deviation Schedule
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Dale R. Crockett TITLE Area Superintendent DATE October 23, 1978

*(See Instructions and Spaces for Additional Data on Reverse Side)

BH/de

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: *"Sacks Cement":* Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Redbed	0	632	
Salt	632	1469	
Salt & Anhydrite	1469	2220	
Anhydrite	2220	2375	
Anhydrite & Dolo.	2375	2629	

38. GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Top Salt	501	
Base Salt	1670	
Yates	1826	
7 Rivers	2150	

★ U.S. GOVERNMENT PRINTING OFFICE: 1974-780-680/VIII-238