

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR Phillips Oil Company
(Succ. to General American Oil Co.)

3. ADDRESS OF OPERATOR
Room 401, 4001 Penbrook St., Odessa, TX 79762

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit F, 1345' FNL & 1880' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☒
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-19-84: 3460' PTD RU WSU. COOH w/rods & pmp. Installed BOP. Tagged TD @ 3228'. Last test pmpd 24 hrs, 8 BO, 20 BW.
6-20-84: WIH w/4 3/4" bit to 3228'. CO to 3231'. Circ-hole clean, rec'd cast iron metal filings.
6-21-84: Tagged BP @ 3238' w/wireline. Dumped 8' of hydromite on top of BP. WIH tagged plug @ 3238'. WIH w/EZ drill BP, set @ 3236'. Ran wire line, tagged plug @ 3231'. Dumped 6' hydromite on top of plug. Tagged top @ 3225'.
6-22-84: Loaded csg w/2% KCL wtr. Perf'd csg from 2317' - 2684'. Set Loc-set plug @ 2750' & Model "R" pkr @ 2730'.
6-23-84: Tst'd plug to 1100#, pmpd 100# sand on plug. Moved pkr to 2235'. Displaced tbg w/375 gals of acid. Leak in welded bell nipple.
6-24-84: SI 24 hrs.

Subsurface Safety Valve: Manu. and Type

N/A

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Mueller TITLE Sr. Engineering Specialist DATE July 18, 1984

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY: JUL 24 1984

Carbide, NEW MEXICO *See Instructions on Reverse Side

5. LEASE LC-028784-C	RECEIVED BY JUL 26 1984 O. C. D. ARTESIA, OFFICE
6. IF INDIAN, ALLOTTEE OR TRIBE NAME ---	
7. UNIT AGREEMENT NAME ---	
8. FARM OR LEASE NAME Keely C Fed	
9. WELL NO. 53	
10. FIELD OR WILDCAT NAME Grayburg Jackson (SR-O-Gb-SA)	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 26, T-17-S, R-29-E	
12. COUNTY OR PARISH Eddy	13. STATE NM
14. API NO. 30-015-22573	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3590' RKB, 3580' GR	

6-25-84: Repaired leak.
 6-26-84: Tst'd csq to 1000#. Trt'd perts 2317' - 2620' w/4125 gals 7 1/2% NEFE HCL containing clay stabilizer & fines suspender. Swbd 5 hrs, 80 BLW.
 6-27-84: Swbd 10 hrs, 5 BO, 20 BLW.
 6-28-84: Frac'd GB/SA w/52,000 gals 40# x-linked KCL wtr w/68,000# 20/40 & 36,000# 10/20 sand.
 6-29-84: 1400 PSI pressure. Flowed well to pit.
 6-30-84: Flowed 210 BLW in 24 hrs.
 7-1-84: Flowed 300 BLW in 24 hrs.
 7-2-84: Unseat 5.5" Model R pkr. Circ 150' sand off 5.5" Loc-set BP. Retrieved B. P. COOH w/2 7/8" tbg, BP & pkr. LD 2 7/8" tbg. Ran 108 jts 2 3/8" tbg w/SN. Tbg set @ 3171'. SN 3172". Removed BOP & installed WH.
 7-3-84: Pmpd 15 hrs, no oil, 72 BLW.
 7-4-84: Pmpd 24 hrs, no oil, 93 BLW.
 7-5-84: Pmpd 24 hrs, no oil, 95 BLW.
 7-6 thru 7-8-84: Pmpd 72 hrs, no oil, 273 BLW.
 7-9-84: Pmpd 24 hrs, 24 BO, 65 BLW.
 7-10-84: Pmpd 24 hrs, 18 BO, 55 BLW.
 7-11,12-84: Pmpd 48 hrs, no test.
 7-13-84: Pmpd 24 hrs, 11 BO, 8.2 BW.
 7-14,15-84: Pmpd 48 hrs, no test.
 7-16-84: Pmpd 24 hrs, 22 BO, 63 BW, GOR: TSTM, Gravity 35.8° from csq perts

2312' - 3172'.
 Job Complete.