

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL ☐ GAS ☐ WELL ☒ OTHER ☐

2. NAME OF OPERATOR

SEP - 1 1978

3. ADDRESS OF OPERATOR

O. C. C.

ARTESIA, OFFIC

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

2135' FSL & 1650' FEL Sec. 26, T-17S, R-30E
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3590.4 GL

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Not to be filled in until completion of well and completion or recompletion report and log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up Rotary Tools, spudded 17 1/4" hole @ 2:15 P.M. 7-20-78. Lost circ. @ 180'.
2. Drilled to 520' KB. Set 12 joints (500') 13-3/8", 48#, H-40 casing with casing shoe @ 502' KB. Cemented with 500 sx Class C w/2% CaCL; dumped 16 yards Redi-mix 3% CaCL down backside of casing. W. O. C. 20 hrs. Installed 12" Shaffer Type B Hydraulic BOP & tested to 1500# prior to drilling cement plug.
3. Drilled 12 1/4" hole to 3612' KB; ran T° survey, spinner survey and caliper log to monitor water flow.. Flow tested 171 BWPD @ approximately 3280' with an open well anomaly @ 2952'. 9-5/8" WIH w/26 Joints (1137') 43.5#, S-95 LT&C csg & 57 joints (2475') 36 1/4" csg with csg shoe @ 3603.61', float collar @ 3558.49', Lynes O.H. pkr (P110-43.5#) @ 2934.25' DV Tool. Cemented as follows: 1st. stage - 400 sx Class H w/.5 of 1% CFR-2 & 3# salt/sx. PD @ 11:30 A.M. 8-1-78. Inflate Lynes pkrs. Salt water flow stopped. Opened DV Tool @ 12:15 P.M., circulated out cement-colored water. Cemented 2nd stage thru DV Tool w/850 sx Howco Lite w/5# Gisonite, 4# Flocele & 2% CaCL. Tailed in w/100 sx Class C w/2% CaCL. PD @ 6:15 P.M. 8-1-78. Cement did not circulate.
4. Ran cement Bond Log. Met with Jim Knauf & discussed Cement Bond Log prior to drilling out cement plug. W. O. C. - 24 Hours. 12"
5. Installed & nipped up Shaffer Type B Hydraulic 3000# BOP & 10" GK Hydrill - 3000#.
6. Drilled 7-7/8" hole to 6076' and ran Yellow Jacket BOP test.

Note: Running & cementing of 9-5/8" casing witnessed by James Brasfield from U.S.G.S office in Artesia.

Will file appropriate forms upon completion of well.

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed by

TITLE Area Supervisor

DATE August 28, 1978

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE AUG 31 1978

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations of Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.