

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

CISE
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other

2. NAME OF OPERATOR

Anadarko Production Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 67, Loco Hills, New Mexico 88255

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2135° FSL & 1650° FEL Sec. 26, T17S, R30E

AT TOP PROD. INTERVAL:

Eddy County, N. Mex.

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Complete in Cisco

SUBSEQUENT REPORT OF:

RECEIVED
OCT 23 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up pulling unit. Loaded tubing w/3% KCL water to kill well. Removed X-tree & installed BOP.
2. Upset pkr & pulled to 9700'KB. Circulated hole w/9.4#/gal 3% KCL pkr fluid. TOH w/pkr
3. Vann set wireline-set CIBP @ 11010'KB; dumped 35' cement on CIBP (11010'-10975'KB) with dump-bailer to abandon Morrow Zone.
4. Vann perforated Cisco Zone 9510-20, 9526-28, 9549, 9552, 9558-63, 9566-70 & 9574-84 @ 2 SPF Total = 73 - .5" diam holes.
5. Ran Halliburton 4 1/2" RBP & RTTS pkr; tested tbg to 6000'; set RBP @ 9630'KB & RTTS pkr @ 9445'KB.
6. Removed BOP & installed X-Tree.
7. Pumped 250 gals 20% NE acid & broke perms down @ 4300' AR&P=2 BPM @ 3000'. Acidized w/4000 gals 20% HCL (NE-FE) acid & 145 BS. AR&P= 5.9 BPM @ 5450'. Shut well in overnight.
8. Swabbed & Flow tested well several days. RDPF.

NOTE: Will file Subsequent report after RBP & RTTS are removed.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE Area Supervisor

DATE October 21, 1981

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

NOV 25 1981
C. C. D.
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO