

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC 42-26 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Viking Energy Corporation ✓	8. FARM OR LEASE NAME Arco-Federal
3. ADDRESS OF OPERATOR 726 First National Bank Bldg., O.C.C. OCELSA, TEXAS 79761	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. Place location as follows: 100' INL, 1980' FEL	10. FIELD AND NAME OF WILDCAT Craybury
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) DF 3950'
	12. COUNTY OR PARISH 13. STATE Eddy New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACTURE TREAT	☐	FRACTURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	(Other)	☐
(Other)	☐	(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12-22-78

Pursuant to conversation between Mr. Jim Knauf and Mr. Roy K. Valla on 12-14-78, the following procedure is recommended to plug and abandon:

1. Set cast iron bridge plug at 2280' with 35' cement on top. (3 sx. cement)
2. Spot 25 sack cement plug (50' in and 50' out) at 4½" casing stub. Estimated to be approximately 1800'.
3. Spot 35 sack cement plug at 860'. (Surface casing at 810')
4. 20' cement plug at surface.
5. Erect pipe marker with following:
Viking Energy Corporation
Arco-Federal #1
Sec. 10, 17 S, 31 E

18. I hereby certify that the foregoing is true and correct

SIGNED Roy K. Valla TITLE Vice President DATE 12-20-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: