

N.M.O.C.D. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on reverse side)Form approved
Budget Bureau No. 42 R1424
5. LEASE DESIGNATION AND SERIAL NO.

LC-053259-A

6. IF INDIAN, ALLIANCE OR INDIAN NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ OIL WELL ☒ GAS WELL ☐ OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR GENERAL AMERICAN OIL COMPANY OF TEXAS		8. FARM OR LEASE NAME ARTESIA, OFFICE	
3. ADDRESS OF OPERATOR P.O. BOX 128, LOCO HILLS, NEW MEXICO 88255		9. WELL NO. 4	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FNL and 1650' FEL		10. FIELD AND POOL, OR WILDCAT GRAYBURG-JACKSON O.S. SA	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3637.6' G.L.	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 28, T-17S, R-30E.	
		12. COUNTY OR PARISH EDDY	
		13. STATE NEW MEXICO	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☒	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) <u>Perforate Casing</u>	<u>XXX</u>
(Other)		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- Spud Well @ 11:00 A.M. March 26, 1980
- Ran 8 5/8" O.D. 20# Casing to 510' K.B. as follows:
 - Volume of Cement was 350 sacks (circulated).
 - Brand of cement was SOUTHWESTERN CLASS "C" with 2% CaCl.
 - Approximate temp. of Cement Slurry was 58°F.
 - Formation Temp. was 66°F.
 - Tested to 1,000# for 30 min. after 18 Hours.
 - Drilled out Cement.
- Ran 5 1/2" O.D. 15.5# Casing to 3190 K.B. and cemented with 125 sacks of Class "C" neat cement and 425 sacks of Class "H" with 10# sand, 5# Salt, and 1/2 of 1% CFR-2 per sack.
- Perforated as follows:

2348'-2356'	(16 Holes)
2597'-2607'	(20 Holes)
2844'-2850'	(12 Holes)
3069'-3079'	(20 Holes)
- Well was treated as follows:
 - Perforations 2348'-2356' 20,000 Gallons of Gelled water containing 20,000 # Sand.-----OVER-----

18. I hereby certify that the foregoing is true and correct

SIGNER Lendell N. Hawkins TITLE Asst. Field Superintendent DATE June 20, 1980
Lendell N. Hawkins

(This space for Federal or State office use)

APPROVED BY John W. Christ TITLE ACTING DISTRICT ENGINEER DATE JUN 26 1980
CONDITIONS OF APPROVAL, IF ANY:

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated on the general and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include special information as is required by local Federal and or State office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present, former or fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below cement and above plugs; amount, size, method of placing of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well was conditioned for final inspection looking to approval of the abandonment.

GPO 640

- b. Perforations 2597'-2607' 20,000 Gallons of Gelled Water containing 20,000# of Sand.
- c. Perforations 2844'-2850' 20,000 Gallons of Gelled Water containing 20,000# of Sand.
- d. Perforations 3069'-3079' 20,000 Gallons of Gelled Water containing 20,000# of Sand.