

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 046044

6. IF INDIAN, AGENCY AND TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☒ GAS ☐  
WELL WELL OTHER

2. NAME OF OPERATOR

Marbob Energy Corporation

3. ADDRESS OF OPERATOR

P.O. Box 304, Artesia, N.M. 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

330' FSL &amp; 330' FWL of Sec. 33

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3552 GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Perry Leonard

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Loco Hills

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

33-17S-29E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other) Cement

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2/1/80 TD 3576'. Circulated 2 hours, lay down drill pipe & collars, ran guide shoe, insert float, 10 centrizers, 86 jts. 5½" 15.50# casing, new, landed @ 3576' KB, 3564' GR, pumped 300 sax Class H cement, 5/10 of 1% CFR-2, 5# salt, 10# sand per sack, plug down @ 6:00 a.m. 2/2/80.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Carolyn Davis*

TITLE

Secretary

DATE

2/2/80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

FEB 4 1980

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED

1982 APR 20 10 10 AM  
FBI - NEW YORK