

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil & Gas Division
811 S. 1st Street
Artesia, NM 88210-2804

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
Designation and Serial No.
LC-046044

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Webb Oil Company

3. Address and Telephone No.

2409 Cerro Road, Artesia, NM 88210-9757

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330 FSL, 330 FWL, Sec 33, T17S, R 29E, Unit Letter M

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Perry Leonard #3

9. API Well No.

30-015-23134

10. Field and Pool, or Exploratory Area

Square Lake Grbg SA

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Notify BLM 24hrs Before starting

1. RH spot 100' plug @ 2400 (perf 2444 to 2782) woc tag *

2. Perf 5 1/2 @ 790 sqz 100' plug (bottom salt @ 740) woc test

4. Perf 5 1/2 @ 375'sqz. 100' plug (8 5/8 shoe @ 310 bottom salt @ 325) woc test

5 spot cmt from 30' to surface

6. cut off well head install dry hole marker

* Onshore Order #2 requires that a cement plug shall be placed opposite all open perforations and extend to a minimum of 50 feet below to 50 feet above the perforated interval or set a CIBP within 50 to 100 feet above the top of the perforations and cap with 35 feet of cement.

14. I hereby certify that the foregoing is true and correct

Signed Alexis C. Swoboda
(This space for Federal or State office use)
(ORIG. SGD.) ALEXIS C. SWOBODA

Title Agent

Date 05/02/01

PETROLEUM ENGINEER

Title

Date MAY 22 2001

Approved by
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS ATTACHED