

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TR  
(Other instructi  
verse side)CATE  
OR FEForm approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-054988-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Berry/Federal "A"

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Grayburg Gales SR-Q-G-SH

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 21, 17S, 30E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1.

OIL  
WELL ☒ GAS  
WELL ☐ OTHER

RECEIVED

2. NAME OF OPERATOR

Petroleum Corporation of Texas

3. ADDRESS OF OPERATOR

Box 911, Breckenridge, Texas 76024

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

990' FNL &amp; 2200' FWL

.5 miles north of post office in Loco Hills and 24.7 miles  
east of Artesia.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3661' GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Running casing-8-5/8" & 4-1/2"  
(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-14-80 - Ran 11 joints of 8-5/8" K-55 24# casing. Set at 516' and cemented with 350 sacks of Class C 2% CCL cement. Filled top with 8 yards of ready-mix cement.

6-21-80 - Set 4-1/2" 10.5# casing at 3642' with DV tool at 2168'. Cemented with 475 sacks of Class H cement in two stages. Additional reports will follow when well is completed.

ACCEPTED FOR RECORD

AUG 15 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Clave Sims

TITLE

Engineering Assistant

DATE

8-5-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side