

After

IPANY Mack Energy Corporation

Perforate 4½
at 60' circ.
to-surface

LEASE & WELL NO. McIntyre A #10

FORMATION _____

COUNTY & STATE Eddy, NM



RAYMOND MALDONADO
SUPERVISOR, P & A OPERATIONS
BUS. (505)393-9171
FAX (505)393-3848
MOBILE (505)390-0540

8 5/8 510' cmt. w/215 sxs circ.

Perforations 560' squeeze w/40 sxs cement

Spot 25 sxs cement at yates 1240'

Set 4½ C.I.B.P. at 3050' cap w/30' cement

Oper. perforations 3092-97

C.I.B.P. 3200' w/30' cmt. 3-20-96

C.I.B.P. 3250' w/30' cmt. 11-20-80

C.I.B.P. 3496' w/30' cmt. 9-30-80

C.I.B.P. 3980' w/30' cmt. 8-19-80

C.I.B.P. 4460' w/30' cmt. 8-3-80

C.I.B.P. 4598' w/30' cmt. 7-29-80

4680' P.B.T.D.

4700' T.D. cmt. w/2777 sxs T.O.C. 1100'

4½ casing 4700'

CONVERSION FACTORS

MULTIPLY	By	TO OBTAIN
Barrels	5.6146	Cubic Feet
Cubic Feet	7.4806	Gallons
Gallons	0.1337	Cubic Feet
Pounds/gal.	7.4806	Pounds/Cu. Ft.

PIPE VOLUMES

0.00545 x I.D.² in inches	= Cu. Ft./Ft.
0.0407 x I.D.² in inches	= Gals./Ft.
0.00097 x I.D.² in inches	= Bbls./Ft.

HYDROSTATIC PRESSURE

FOR WATER:
0.434 x Depth in Feet = PSI.
FOR OTHER FLUIDS:
0.434 x Depth x Sp. Gr. = PSI.