

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

MMOCD  
811 S.1st

Artesia, N.M. 88210 **SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 20 T-17-S R-30-E 990 FSL 2310 FEL

RECEIVED

JUL 24 1996

OIL CON. DIV.  
DIST. 2

5. Lease Designation and Serial No.

LC-057634

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

McIntyre A #10

9. API Well No.

30-015-23382

10. Field and Pool, or Exploratory Area

Grayburg Jackson 7RVS-

11. County or Parish, State

QGGB-SA

Eddy, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- (1) Set 4½ C.I.B.P. at 3050' cap w/35' cement
- (2) Load hole w/mud
- (3) Spot 25 sxs cement plug at top of Yates 1240'
- (4) Perforate 4½ casing at 8 5/8 shoe 50' below 560' squeeze w/40 sxs cement and tag
- (5) Perforate 4½ casing at 60' circulate cement to surface-set P.A. marker

14. I hereby certify that the foregoing is true and correct

Signed Raymond Maldonado Title Supervisor

Date 7-16-96

(This space for Federal or State office use)

Approved by David R. Glass

Title PETROLEUM ENGINEER

Date JUL 18 1996

Conditions of approval, if any:

SEE ATTACHED