

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 054988 (A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

JUL 15 1981

8. FARM OR LEASE NAME

Berry Federal O. C. D.

9. WELL NO.

ARTESIA, OFFICE

6

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson SR-Q-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21, 17S, 30E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Petroleum Corporation of Texas

3. ADDRESS OF OPERATOR

Box 911, Breckenridge, Texas 76024

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

At surface

Unit letter E, 2310' FNL & 990' FWL of Sec. 21, Twp. 17S,

Rge. 30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3647' GR; 3657' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☒
☒
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Running casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-29-81 - Ran 12 joints 8-5/8" 24# casing; set at 495' with 325 sx. Clars C, 2% CC.

4-8-81 - Ran 4-1/2" 10.5# K-55 casing and set at 3604' with 175 sx. Howco Lite and 500 sx. H.

5-19-81 - Perforated 28 shots from 3292-3367'.

5-20-81 - Acidized with 3000 gals. 15% acid.

5-21-81 - Frac'd with 16,000 gals. 20/40 sd. per stage in two stages.

18. I hereby certify that the foregoing is true and correct

SIGNED Ladean Rayland

TITLE Production Clerk

DATE 7-7-81

(This space for Federal or State)

APPROVED BY ROGER A. CHAPMAN

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JUL 13 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side