

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

0-29020C

6. IF INDIAN, ALLOTTEE OR TRIBAL LAND

JUN 17 1981

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dale H. Parke "O. C. D. ARTESIA, OFFICE"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson (SR, Q, G, SA)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15, T-17-S, R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

1100 Wall Towers West, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface

990' FSL & 990' FEL

Sec. 15, T-17-S, R-30-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3688.3' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set 5 1/2" production csg

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drill 7 7/8" hole to 3550'. CCM to run csg. Ran 88 jts 5 1/2" 14# J-55 ST&C csg. Set @ 3550'. Csg pkr @ 2567'. DV tool @ 2527'. Cmt w/300 sxs Class "C". PD @ 6:45 A.M. 6-4-81. Circ. 70 sxs cmt, w/3000 sxs Light wt cmt + 20# salt/sx & 100 sxs Class "H". Circ 250 sxs. Over displaced cmt. Cmt thru DV w/400 sxs Class "H" & 200 sxs Class "H". Closed DV tool. PD @ 10:30 A.M. WOC. Compressive strength of Class "H" after 24 hours is 4050 psi @ 110°F BHT.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Operations Manager DATE 6-9-81

(This space for record of State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF AGENCY

JUN 12 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side