

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029020C

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

AUG 11 1981

8. FARM OR LEASE NAME

Dale H. Parke "C" OFFICE

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson (SR, Q, G, SA)

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 15, T-17-S, R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1a. TYPE OF WELL:

OIL WELL

☒

GAS WELL

☐

DRY

☐

Other

b. TYPE OF COMPLETION:

NEW WELL

☒

WORK OVER

☐

DEEP-EN

☐

PLUG BACK

☐

DIFF. RESVR.

☐

Other

AUG 5 1981

2. NAME OF OPERATOR

Southland Royalty Company /

3. ADDRESS OF OPERATOR

1100 Wall Towers West, Midland, TX 79701 ROSWELL, NEW MEXICO

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 990' FSL & 990' FEL, Sec. 15, T-17-S, R-30-E

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

5-19-81

16. DATE T.D. REACHED

6-5-81

17. DATE COMPL. (Ready to prod.)

6-27-81

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3688.3' GR

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

3550

21. PLUG, BACK T.D., MD & TVD

3540

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

0-TD

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

2653-3510' Grayburg-Jackson (SR, Q, G, SA)

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

CNL/FDC/GR-Caliper

DLL/MLL/SFL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	450'	12 1/4"	420 sxs cement	5 sxs Circ.
5 1/2"	14#	3550'	7 7/8"	300 sxs cement	70 sxs Circ.
		DV @ 2527		3700 sxs cement	250 sxs

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8	3448	3433 (SN)

31. PERFORATION RECORD (Interval, size and number)

1 JSPF 3500-3510 also @ 3066, 64, 62, 56
3366-3382 54, 52, 34, 2979, 76, 74
3343-3360 72, 34, 32, 30, 2885, 83,
3328-3340 31, 06, 04, 02, 2778,
3304-3308 2685, 83, 73, 53.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3304-3510	Acdz w/1210 gal. 15% NE Acid
3304-3510	Frac w/54,000 gal. gelled H ₂ O &
2653-3066	59750#SD: Acdz w/5000 gal 15% NE
2653-3066	acid. Frac. w/40,000 gal gelled H ₂ O

33.* PRODUCTION & 60,000 #SD.

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
6-21-81		Initially flowing then pumping 2"x1 1/2" x 12'				Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
7-24-81	24	---	→	103	----	190	----
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
----	----	→	103	----	190	37	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

NA

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

Electric logs

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Aug 6 1981
Engineer Tech.

DATE

8-3-81

*(See Instructions and Spaces for Additional Data on Reverse Side)

ACCEPTED FOR RECORD
ROGER A. CHAPMAN
GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 32.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
				Base Salt	1115'	
				Yates	1300'	
				Queen	2230'	
				Grayburg	2594'	
				San Andres	2926'	