

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Tenneco Oil Company /
3. ADDRESS OF OPERATOR
6800 Park Ten Blvd., San Antonio, TX 78213
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1840' FNL & 1980' FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) spud and set casing

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
SEP 8 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE NM-0397623
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Federal KL-17
9. WELL NO. 1
10. FIELD OR WILDCAT NAME Undes. So. Empire Morrow
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA Sec. 17, T17S, R29E
12. COUNTY OR PARISH Eddy
13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3625' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/23/81 Spud well at 6:00 A.M. Ran 10 jts 13-3/8", 54 5/8" x 55" STC csg. at 407'. Cmt. w/535 sxs Cl "C" + 2% CaCl₂. Recent 1" w/35 sxs, circ to surf. WOC 8 hrs.
8/29/81 Ran 63 jts 9-5/8", 23-1/2", N-80, 8RD LTC csg at 2608', cmt w/300 sxs class C, 2% KCL-yield 1.32, 14.8#/gal, top of cmt at 1065'. Cmt thru 1" w/1300 sxs NOWCO lite, class C, 2% KCL, cmt top w/458 sxs Cl C NOWCO lite, 10# salt, 1/4 Flooole, 2% KCL, 1.84 yield, 12.4# gal. Pump plug down w/191 bbl H₂O. Circ to surf. WOC 12-1/2 hrs.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED

Roger A. Chapman
ACCEPTED FOR RECORD
ROGER A. CHAPMAN

TITLE Production Analyst DATE September 2, 1981

APPROVED BY
CONDITIONS OF APPROVAL IF ANY

SEP 8 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or other-wise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.