

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COMMISSION
SUBMIT IN TRIPLE
DRAWING INSTRUCTIONS
Artesia, NM 88210

Form approved.
Budget Bureau No. 42-R1424.

5F/7 file

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
BURNETT OIL CO., INC.

3. ADDRESS OF OPERATOR
Box #198, Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980' f. North and 2080' f. West lines of
Sec. 1-17S-30E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3729.5 Gr.

5. LEASE DESIGNATION AND SERIAL NO.
NM-2747 RECEIVED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
O. C. D.

8. FARM OR LEASE NAME
JACKSON "B" ARTESIA, OFFICE

9. WELL NO.
33

10. FIELD AND POOL, OR WILDCAT
Square Lake - GB-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 1-17S-30E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

RECEIVED
APR 26 1982

MAY 13 1982

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On Nov. 24, 1981, cemented 8-5/8" O.D. 24# J-55 casing at 452' with 300 sacks Class C cement + 2% CaCl. Cement circulated to surface.

On Nov. 29, 1981, cemented 5 1/2" O.D. 15.5# J-55 casing at 3220' with first stage of 120 sacks Class H + .5% CF-R2 + 8# salt/sx. Centralizers on bottom 7 joints. DV collar at 2540' with umbrellas above and below.

On Dec. 3, 1981, cemented thru DV collar with 400 sx. Class H cement with 10# salt/sx + 100 sx. Class H with 4% CaCl. Water flow on outside of 5 1/2" successfully shut off.

Squeezed DV collar with 200 sx. Class H cement with 6% gel + 250 sx. Class H + 3% CaCl. No flow back after WOC.

Water Flows: 2450' - Estimated 2,563 BPD.
2530' - Estimated 10,285 BPD.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ralph L. May

TITLE

Consulting Engineer

DATE Apr. 22, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

MAY 7 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In-addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.