

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029339(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Artesia Petroleum Co.

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Square Lake Pool

11. SEC., T., R., M., OR BLK. AND
SURVEY OR ARMA

Sec. 1, T17S-R30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Lucille F. McKinley

3. ADDRESS OF OPERATOR

P. O. Box 2145 Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

890' FNL & 890' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3762.7 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Casing Program

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud In 6/11/81 with 12 1/4" hole, Drill to T.D. of 382'. Ran 9 jts., 369.71' of 8 5/8", 23#, L. B. Foster new casing. Set at 382' with Texas Pattern shoe, insert float, 2 centralizers. Circulate 375 sacks class "C" cement. Pressured up casing & BOP to 1000# for 30 minutes which tested all right. Drilled out below surface casing with a 7 7/8" hole to a total depth of 3320'. T.D. reached on 6/13/81. Ran 79 jts. (3310') of 4 1/2", 10.5# new casing with auto fill float shoe, latch down plug, 10 centralizers. DV tool set at 2891'. See Exhibit "A" for details of cementing program.

RECEIVED
OCT 8 1981OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

ACCEPTED FOR RECORD
ROGER A. CHAPMAN

(This space for Federal or State office use)

TITLE Operator

DATE October 6, 1981

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side