

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-028793-b

6. IF INDIAN, ALLOTTEE OR TRUST NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Burch "B" NOV 2 1981

9. WELL NO.

34

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson SR-0-5-1A

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 23, T-17S, R-29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

General American Oil Company of Texas

3. ADDRESS OF OPERATOR

P. O. Box 128 Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface

2310' FSL and 330' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, OR, etc.)

3605' KB

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Production Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-15-81 Ran 5-1/2" 15.5# K-55 and set @ 3240' (T.D.). Cemented with 220 sacks of Class "H" cement with 10# sand, 5# salt, 1/4# Flocele, and 3/4 of 1% CFR-2. Open DV tool @ 2320' and circulate.

9-18-81 Pump 250 sacks Class "C" cement with 6# salt through DV tool. Displace cement. Waterflow through 8-5/8" casing and 5-1/2" casing shut-off.

10-15-81 Drill out cement and DV tool. Pressure test casing — casing held pressure, DV tool closed.

OCT 20 1981

OCT 21 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

ACCEPTED FOR RECORD  
SIGNED ROGER A. CHAPMANTITLE EngineerDATE October 21, 1981

(This space for Federal or State office use)

APPROVED BY OCT 29 1981  
CONDITIONS OF APPROVAL, IF ANY:U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side