

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

C/SF

LC-031844

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Ray Westall		8. FARM OR LEASE NAME Arco Federal	
3. ADDRESS OF OPERATOR P. O. Box 4 Loco Hills, NM 88255		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit Letter O 660 FSL 1980 FEL		10. FIELD AND POOL, OR WILDCAT Grayburg/Jackson	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 1, 17S, 31E	
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 4007.8		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐


(Other) Running Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

October 28, 1981 - Spud well with 11" bit. Changed to 7 7/8" bit on 10-29-81. Ran 655' of 8 5/8" OD, 8 rd, 20# casing. Cemented with 420 sx of Class "C" 2% CaCl cement. Circulated 100 sx to surface. WOC 18 hours. Pressured up tp 1000# for 30 minutes. Held O.K.

November 5, 1981 - T. D. 4300'--- Ran 4300' 4 1/2" 10-5 8 rd casing. Set and cemented with 1000 sx 35/65 poz mix with 2% gel and 5# salt/sx. Cement circulated to surface. Float held. WOC 24 hours.



U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

ROGER A. CHAPMAN

TITLE

Operator

DATE

11-23-81

(This space for Federal or State office use)

APPROVED BY

DEC 11 1981

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side