

NM OIL CONS. COMMISSION
Drawn BY UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR CATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 034696

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Vola Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Und. Dry Run Jackson
Robinson11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, T-17S, R-31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Ray & Garel R. Westall ✓

O. C. D.
ARTESIA OFFICE

3. ADDRESS OF OPERATOR

P.O. Box 4 Loco Hills, NM 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 2180' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4003. GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-30-82 Spud with 11" bit.

5-7-82 Drilled to 637'. Ran 625' of 8 5/8" casing. Set at 637'. Cemented with 500 sx Class "C" 2% CaCl. Circulated 200 sx to surface. Changed to 7 7/8" bit.

5-14-82 TD 4300'

Ran 4300' 4 1/2" 10.5# 8 rd casing. Set and cemented at 4300' with 500 sx 50-50 Poz. 500 sx Pacesetter-C 5# salt. Circulate.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray Westall

TITLE

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 24 1982
OperatorU.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICORECEIVED
MAY 21 1982OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

DATE 5-19-82

DATE