

45F

NM OIL CONS. COMMISS.
Drawer DD
SUBMIT IN TRIPLICATE*
(ON reverse side)
Antesia (NM 88210)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0384575

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dale H. Parke "A" Tr. 1

9. WELL NO.

13

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson (SR,Q,G,SA)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 15, T-17-S, R-30-E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

21 Desta Drive, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

2260' FSL & 1650' FWL, Sec. 15, T-17-S, R-30-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3688.8' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

FULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set 8 5/8" Surface Csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 12 1/4" hole 10:00 AM 2/4/83. Drilled to 440'. CCM to run csg. Ran 10 jts 8 5/8" 24# J-55 ST&C csg. Set @ 440'. Cmt w/350 sx C1 "C" cmt w/2% CaCl. PD @ 1:30 PM 2/5/83. No circ. Wait 4 hrs. Ran 1" pipe on outside of 8 5/8" csg to 280'. Pmp 50 sxs C1 "C" cmt w/4% CaCl. Wait 3 hrs. Tag cmt @ 210'. Pmp 50 sxs C1 "C" cmt w/4% CaCl. Circ 10 sxs. Cut off 8 5/8" csg. Install wellhead & BOP. Test csg & BOP to 1000#. Held Okay. Drill ahead w/7 7/8" bit.

RECEIVED
FEB 8 1983

OIL & GAS
MINERALS LICHT. SERVICE
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED F. N. RAD by D. Roberts

TITLE District Operations Engineer DATE 2/7/83

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY
CONDITIONS OF APPROVAL IF ANY

TITLE

DATE

FEB 11 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

See Instructions on Reverse Side