Form 9-331 (May 1963)

CLINIDAY NO

UNITED STATES Artesia SUBMIT IN TRIPLICATE DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-029020(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

		·-			
TICES	AND	REPORTS.	ON	WFI	15

GEOLOGICAL SURVEY

(Do not use this form for proposa	LES AND REPORTS ON WELLS lls to drill or to deepen or plug back to a different reservoir FION FOR PERMIT— for such perpenting D	·
OIL XX WELL OTHER		7. UNIT AGREEMENT NAME
Name of OPERATORSouthland Royalty Compan	FER 5 0 1303	8. FARM OR LEASE NAME Dale H. Parke "A" Tr. 1
3. ADDRESS OF OPERATOR 21 Desta Drive, Midland, 4. LOCATION OF WELL (Report location cle	Texas 79701 ARTESIA, OFFICE	9. WELL NO. 14 10. FIELD AND POOL, OR WILDCAT
See also space 17 below.) At surface	FWL, Sec. 15, T-17-S, R-30-E	Grayburg-Jackson (SR,O,G,SA) 11. SEC., T., R., M., OR BLE. AND SURVEY OF AREA
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	Sec. 15, T-17-S, R-30-E


16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

entant i appropriate ben to mercare i talette of i tender, itepolif of emercare						
NOT	ICE OF	INTENTION TO:		SUBS	EQUENT REPORT OF:	
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF FRACTURE TREATMENT	REPAIRING WE	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT	
(Other)	Ш. ——	CHANGE PLANS		(Other) Set 8 5/ (Note: Report resu Completion or Reco	8" Surface csg. lits of multiple completion on mpletion Report and Log form	Well

3679.9' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded 12 1/4" hole @ 9:45 AM 2/13/83. Drl to 445'. CCM. Set 8 5/8" csg @ 445'. Cmt w/350 sxs Cl "C" cmt 2% CaCl. PD @ 8:30 PM 2/13/83. Circ 75 sx. Cut off 8 5/8" csg. Install Wellhead & BOP. Test BOP to 1000#. Drilling ahead.



		" "
S. I hereby certify that the foregoing is the	TITLE District Opera	ations Engineer DATE _ 2/17/83
APPROVED BY CONDITIONS OF APPROVED BY	AVID R. Glades:	DATE
MINERALS MANAGEME ROSWELL, NEW M	NT SERVICE EXICO "See Instructions on Reverse Si	d ž