

Dra

Artesia, NM 88210

Form 9-331

Dec. 1973

Form Approved.

Budget Bureau No. 42-R1424

RECEIVED BY

UNITED STATES

JUN 28 1985

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

O. C. D.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR

Phillips Oil Company

3. ADDRESS OF OPERATOR

Rm 401, 4001 Penbrook St., Odessa, Tx 79762

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit L, 1980' FSL &amp; 660' FWL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) Plugback to 3030' & released ☒

to Anadarko Production Company

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 6-07-85: MI & RU. Removed tbq head, welded on pull nipple. RU csg jacks & removed csg hanger. Well kicking thru 8-5/8" csg. Set csg on bottom. Removed csg jacks & nipples up 6" dbl. BOP's. Rigged jacks back up.
- 6-08-85: Stretch free point csg. Cut off csg @ 5100'. POH & laid dwn 5-1/2" csg. RD. (Pulled 125 jts (5054.10' ) of 5-1/2" csg.)
- 6-09-85: Crew off.
- 6-10-85: Bled pressure off well and chg 5-1/2" rams to 2-1/2". Picked up 2-7/8" work string to 5175' (75' below cut-off) Broke circ. Mixed & displaced 40 sx Class C cmt w/2% CaCl across cut-off. Cmt mixed @ 15 ppg.
- 6-11-85: Tagged plug @ 5075'. Displaced hole w/9.5# mud laden brine, spotted 15 sx cmt 5075'-5017', 27 sx 4400'-4295'. 45 sx 3150'-3050'. All plugs Class C w/2% CaCl, mixed @ 15 ppg. WOC 4 hrs, tagged plug @ 3030'. POOH w/2-7/8" tbq.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ n/a \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SEE REVERSE SIDE

SIGNED W. J. Mueller TITLE Sr. Engineering Specialist DATE June 14, 1985

(This space for Federal or State office use) 915/367-1257 (McLemore)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 26 1985

6-12-85: Nipped down & set off BOP's. RD & MOR. Cleaned up location.  
Job complete. Well released to Anadarko 6-12-85 for possible  
shallow completion.