


UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

30-015-24947

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1A. TYPE OF WORK DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/>			5. LEASE DESIGNATION AND SERIAL NO. LC-028731 (A)
1B. TYPE OF WELL OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>			6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR Marbob Energy Corporation			7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P.O. Drawer 217, Artesia, N.M. 88210			8. FARM OR LEASE NAME M. Dodd "A"
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.) At surface 330 FSL 330 FWL At proposed prod. zone Same			9. WELL NO. 35
14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE 20 air miles east of Artesia, N.M. 88210			10. FIELD AND POOL OR WILDCAT Grayburg Jackson - 58-8-G-5A
15. DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drig. unit line, if any) 330'			11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 14-T17S-R29E
16. NO. OF ACRES IN LEASE 600			12. COUNTY OR PARISH 13. STATE Eddy N.M.
17. NO. OF ACRES ASSIGNED TO THIS WELL 40			
18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 660'			20. ROTARY OR CABLE TOOLS Rotary
19. PROPOSED DEPTH 3450'			22. APPROX. DATE WORK WILL START* 8/1/84
21. ELEVATIONS (Show whether DF, RT, GR, etc.) 3623.5' GR			



PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12 1/4"	8 5/8"	24#	350'	Sufficient to circulate
7 7/8"	5 1/2"	15.50#	3450'	450 sax, to base of salt

Pay zone will be selectively perforated & stimulated as needed for optimum production.

Attached are: 1. Location & acreage dedication plat
2. Supplemental drilling data
3. Surface use plan

Post ID-1
8-3-84
APF & BK

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24. SIGNED Sarah Orie TITLE Production Clerk DATE 7/18/84
(This space for Federal or State office use)

PERMIT NO. APPROVAL DATE
APPROVED BY TITLE AREA MANAGER
CONDITIONS OF APPROVAL, IF ANY: CARLSBAD REGIONAL DATE 7-26-84

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS
ATTACHED

**NEW MEXICO OIL CONSERVATION COMMISSION
WELL LOCATION AND ACREAGE DEDICATION PLAT**

Form C-102
Supersedes C-128
Effective 1-1-65

All distances must be from the outer boundaries of the Section


Operator Marbob Energy Corporation			Lease M Dodd A		Well No. 35
Section 14	Township 17 South	Range 29 East	County Eddy County		
Actual Endage Location of Well: 330 feet from the South line and 330 feet from the West line					
Ground Level Elev. 3623.5	Producing Formation San Andres	Pool Grayburg Jackson SR-Q-G-SA		Dedicated Acreage: 40 Acres	

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☐ Yes ☐ No If answer is "yes," type of consolidation _____

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) _____

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.



CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Carolyn Orris
Name

Carolyn Orris

Position

Production Clerk

Company

Marbob Energy Corporation

Date

5/31/84

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed

May 24, 1984

Registered Professional Engineer
and/or Land Surveyor

John W. West

Certificate No. **JOHN W. WEST, 676**
RONALD J. EIDSON, 3239

0 330 660 990 1320 1650 1980 2310 2640 2970 3300 3630 3960 4290 4620 4950 5280 5610 5940 6270 6600

REGAN OFFSHORE INTERNATIONAL, INC.

Torrance,


ANNULAR

REGAN BLOWOUT PREVENTERS

The Regan Torus Blowout Preventer is used primarily on production and workover rigs for well control up to 3000 PSI working pressure.

DESIGN FEATURES

- The Torus Preventer is designed for minimum height to facilitate its use with production and workover rigs.
- The rubber packer will conform to any size hole in the well bore. Sealing ability is not affected by minor damage to the inner bore.
- The packer will seal an open hole at full working pressure.
- The dual packer design increases the reliability of the preventer since the outer rubber is never exposed to the well bore. Under ordinary service, the outer packer is rarely replaced.

TORUS BLOWOUT PREVENTER
PATENTED

SPECIFICATIONS

Nominal Size	Test Pressure (PSI)	DIMENSIONS (in.)				Weight (lbs.)	End Flanges (1)	R/X Ring Grooves	Side Outlet
		Outside Diameter	Inner Bore	Overall Height					
6	1000	24	20 1/2	39 1/4		1400	2000	15	None
8	1500	30	26 1/2	41 1/4		1900	2000	15	2" L.P.
10	2000	36	32	45		2400	2000	15	None

1. Bottom flange
2. Top flange
3. Side flange
4. Side flange
5. Side flange
6. Side flange
7. Side flange
8. Side flange
9. Side flange
10. Side flange

SUP Exhibit "F"

REGAN BLOWOUT PREVENTER
Marbob Energy Corporation
Well #35 M. Dodd "A" Federal
SW#SW# Sec. 14-17S-29E.

SUPPLEMENTAL DRILLING DATA

MARBOB ENERGY CORPORATION
WELL #35 M. DODD "A" FEDERAL
SW1/4SW1/4 SEC. 14-17S-29E
EDDY COUNTY, NEW MEXICO
(DEVELOPMENT WELL)

1. SURFACE FORMATION: Quaternary.
2. ESTIMATED TOPS OF GEOLOGIC MARKERS:


Salt	360'	Queen	1815'
Base Salt	780'	Grayburg	2140'
Yates	930'	San Andres	2510'
Seven Rivers	1145'	Glorietta	3900'
3. ANTICIPATED POROSITY ZONES:

Water	Above 180'
Oil	2350 - 3450'
4. CASING DESIGN:

SIZE	INTERVAL	WEIGHT	GRADE	JOINT	CONDITION
8 5/8"	0-350'	24.0#	K-55	STC	New
5 1/2"	0-3450'	15.5#	K-55	STC	New
5. SURFACE CONTROL EQUIPMENT: A double ram-type or annular BOP will be used. (See diagram attached as Exhibit "F")
6. CIRCULATING MEDIUM:

0 - 350'	Fresh water mud with gel or lime as needed for viscosity control.
350' - 3450'	Salt water mud, conditioned as necessary for control of viscosity and water loss or gain.
7. AUXILIARY EQUIPMENT: Drill string safety valve.
8. LOGGING PROGRAM: CNL-FDC W/GR Log will be run to TD.
9. ABNORMAL PRESSURES, TEMPERATURES OR GASES: A water flow may be encountered in the salt section.
10. ANTICIPATED STARTING DATE: It is planned that operations will commence about August 1 1984. Duration of drilling, testing and completion operations should be one to four weeks.

SW $\frac{1}{4}$ SE $\frac{1}{4}$ Section 14-17S-29E.



LEGEND

(1cm = 88ft)

Primary Line
Proposed Line

SUP Exhibit "E"

SKETCH OF ELECTRIC POWER

LINES

Marbob Energy Corporation

Well #35 M. Dodd "A" Federal

SW $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 14-17S-29E.

