

RECEIVED BY  
Form 9-331  
Dec. 1973  
SEP 17 1984  
O. C. D.  
ARTESIA, OFFICE

NM OIL CONS. COMMISSION  
Lawer DD  
Artesia, NM. 88210

Form Approved.  
Budget Bureau No. 42-R1424

C/SF

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Phillips Oil Company ✓

3. ADDRESS OF OPERATOR

4001 Penbrook St., Odessa, Texas 79762

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FS & 660' FE lines

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Spud well and set surface casing

SUBSEQUENT REPORT OF:

☒

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

LC-028784-C

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keely-C Fed

9. WELL NO.

58

10. FIELD OR WILDCAT NAME

Grayburg-Jackson (SR-Q-GB-SA)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 25, T-17-S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

30-015-24976

15. ELEVATIONS (SHOW DF, KDB, AND WD)

GR 3588.5 (Unprepared)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/7/84 Complete construction of location. Set 40' 16" conductor pipe & cmt to surface.

9/8/84 MI & RU Cactus Drilling Rig. Spud 12-1/4" hole 9/8/84.

9/9/84 Ran 10 jts. (395') 8-5/8" OD 24# K-55 ST&C csg - set @ 372' KB. Cmt'd w/350 sk Dowell Class "C" w/2% CaCl<sub>2</sub> mixed @ 14.8 ppg. Circ. 100 sk. WOC 8 hrs. Test csg to 600# for 30 mins. OK.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ralph J. Roper W.J. Mueller TITLE Sr. Engineering DATE 9/12/84  
Specialist

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL SEP 13 1984

Carlsbad, NEW MEXICO

\*See Instructions on Reverse Side