

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Getty Oil Company

3. ADDRESS OF OPERATOR
P. O. Box 728, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
2560' FSL & 2630' FEL
AT SURFACE: (Unit Letter 'J')
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE

LC-029419-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Skelly Unit

8. FARM OR LEASE NAME

Skelly Unit

9. WELL NO.

156

10. FIELD OR WILDCAT NAME SR-2-6-SH

Grayburg Jackson ~~Fren-7 Rivers~~

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 22, T-17-S, R-31-E

12. COUNTY OR PARISH

Eddy

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3845.6 (GR)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TOTAL DEPTH 3685'

8 5/8" OD 28# K-55 CSG SET @ 511'

1. Ran 3671' (96 jts.) 5 1/2" OD 17# K-55 csg & Set @ 3685'.
2. Cemented 1st stage W/200 sx class H Cement containing 6# Salt & .3% CFR-2 per sack.
3. With DV Tool open @ 2890' cemented 2nd stage W/775 sx LW Cement followed W/375 SX Class H Cement. Cement did not circulate. WOC. DOC.
4. Tested cement from 3540-3647 to 1000# for 30 minutes, 12-30-84. Tested OK.
5. Water flow above 707' from 562-612 & 675-700. Bradenhead squeeze W/1000 gals Flocheck & 300 sx class H Cement containing 5# Salt & 2% CaCl. WOC. Test to 800# 1-6-85. Tested OK.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Baker II TITLE Dist. Opr's Mgr DATE 1-16-85

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

FEB 1 1985

*See Instructions on Reverse Side

NEW MEXICO