

RECEIVED BY

NM OIL CONS. COMMISS ON

Drawer DD

Artesia, NM 88210

LC-20-10 (10)

c/5F

SEP 19 1985

## SUNDRY NOTICES AND REPORTS

O. C. D.

Use this form for proposals to drill or to deepen or to recomplete or to recompletion of a well. Use APPLICATION FOR PERMIT for each proposal.

ARTESIA, OFFICE

WELL ☒ WELL ☐ OTHER

2. NAME OF OPERATOR

TEXACO PRODUCING INC.

3. ADDRESS OF OPERATOR

P.O. BOX 728, HOBBS, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

UNIT LTR. "H", 2600 FNL &amp; 1310' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3848.01

7. UNIT AGREEMENT NAME

Skelly Unit

8. FARM OR LEASE NAME

9. WELL NO.

157

10. FIELD AND POOL, OR WILDCAT

Fren 7-Rivers

11. SEC. T. R. M. OR BLK. AND SURVEY OR AREA

Sec. 22, T071S-R-37E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Completion (Testing)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

## TO COMPLETE FREN SEVEN RIVERS TESTING

1. Rig up.
2. Bridge plug, set at 2890'.
3. Perf 2, 41" squeeze holes at 2460'.
4. Squeezed 5 1/2" perfs at 2460' w/150 sx class "C" w/2% Cacl.
5. Drill cnt. 2418-2460. Spot w/300 gal 10% acetic acid from 2420-2120'. Perfed 5 1/2" csg in 7-Rivers 2163,64,71,72,94,95,2205, 07,09,11,13,15,17,20, 30,32,41,42,54,55,63,65,99, 2301, 03,10,12,23,25,43,45,55,58,60, 2416, 18 (40 holes).
6. Set prk. at 2084'. Treated perfs 2165-2418 w/3000 gal 15% NEFE, 80 balls. POH w/pkr.
7. Ran production equipment. Test well to stabilize production. Final disposition to follow.

18. I hereby certify that the foregoing is true and correct

SIGNED

W.B. L. L.

TITLE

Dist. Opr. Mgr.

DATE

9/5/85

(This space for Federal or State office use)

APPROVED BY

ACCEPTED FOR RECORD

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

SEP 17 1985

\*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO