

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other instructions
on reverse side)


VE
re

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Marbob Energy Corporation ✓		8. FARM OR LEASE NAME M. Dodd "B"	
3. ADDRESS OF OPERATOR P.O. Drawer 217, Artesia, N.M. 88210		9. WELL NO. 51	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1245 FNL 1245 FWL		10. FIELD AND POOL, OR WILDCAT Grbg Jackson SR Q G SA	
14. PERMIT NO. 30-015-25340		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3615.2' GR	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		12. COUNTY OR PARISH Eddy	
		13. STATE N.M.	



16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Plug back	
(Other) ☐			
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			

Perforated as follows: 5400-03-16-23-30-35-44-83-90, 5506-08-18-30-37-46-92, 5602-08-27-52-68-91-99'; acidized zone w/1000 gal. 15% NE acid, swab tested, no show, no fluid entry; set cement retainer @ 5350', squeezed w/100 sax; left 50' cement on top of retainer. Perforated as follows: 5244-5262'-1 HPF, 18 shots; acidized w/1000 gal. 15% NE acid, swab tested, had stain of oil; set cement retainer @ 5200'; squeezed w/100 sax; left 50' cement on top of retainer.

ACCEPTED FOR RECORD

DEC 19 1985

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct		
SIGNED <i>Carlynn Purcell</i>	TITLE Production Clerk	DATE 12/16/85
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		

*See Instructions on Reverse Side