

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other Instructions on reverse side)
CONS. COMM. ON

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC 028992-I

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cedar Lake ADI Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undes. Cedar Lake Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit E, Sec. 26-T17S-R30E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. OIL WELL ☒ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2140' FNL & 660' FWL, Sec. 26-T17S-R30E

14. PERMIT NO.

API #30-015-25494

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3617' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) Intermediate Casing ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-7-86. Ran 107 joints 8-5/8" 32# J-55 ST&C casing set 4507'. 1-Texas Pattern guide shoe set 4507'. Float collar set 4465'. Cemented w/2000 sacks Pacesetter Lite w/8#/sx salt + 1/4#/sx Celloseal. Tailed in w/200 sacks Class C + 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 6:15 PM 1-7-86. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 35 sx to pit. WOC. Drilled out 5:15 PM 1-8-86. WOC 23 hrs. NU and tested to 1000# for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

ACCEPTED FOR RECORD

Gurl
JAN 28 1986

CAPISBAD, NEW MEXICO

RECEIVED BY

JAN 31 1986

O. C. D.

ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Supervisor

DATE 1-23-86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side