

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Drawer DD  
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐  
2. NAME OF OPERATOR  
Siete Oil & Gas Corporation  
3. ADDRESS OF OPERATOR  
P.O. Box 2523, Roswell, NM 88201  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FSL, 1650' FWL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

RECEIVED BY

JAN 2 1986

O. C. D.

ARTESIA, OFFICE

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) Production Casing

5. LEASE  
NM - 14847  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
---  
7. UNIT AGREEMENT NAME  
---  
8. FARM OR LEASE NAME  
Sackett Federal  
9. WELL NO.  
#2  
10. FIELD OR WILDCAT NAME  
Grayburg - Jackson - S R - Q - G - LA  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec: 29, T-17-S, R-29-E  
12. COUNTY OR PARISH 13. STATE  
Eddy New Mexico  
14. API NO.  
30-015-25502  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3598' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12/20/85 - L & M rig #1 T.D. 7 7/8" hole to 3275' -

12/21/85 - L & M rig #1 ran 82 joints 5 1/2", 15.5#, J-55 casing set @ 3263'  
K.B. - cemented w/ 1000 sxs Dowell light weight 3 cement w/10# salt,  
1/4# cellflake - tailed in w/300 sxs 50/50 poz class "C" cement  
w/5# salt - plug down @ 9:30am - circulated 65 sxs cement to surface  
- WOC

*Signature*  
DEC 1 1985

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *L. H. Justice* TITLE Production Supervisor DATE 12/26/85

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY