M' OTT COMS. CLUMESION Form 3160-3 SUBMIT IN 'A CLICATE* Form approved. (November 1983) Budget Bureau No. 1004-0136 (Other instructions on Drawer DD UNITED STATES (formerly 9-331C) reverse side) Expires August 31 Artes DEPARTMENT OF THE INTERIOR LEASE DESIGNATION AND SERIAL NO. BUREAU OF LAND MANAGEMENT LC 074939 APPLICATION FOR PERMIT TO DRILL, DEEPEN, 6. IF INDIAN, ALLOTTER OR TRIBE NAME OR PLUG BACK 1a. TYPE OF WORK DRILL 🖾 PLUG BACK 🗌 7. UNIT AGREEMENT NAME RECEIVED BY b. TYPE OF WELL WELL X MULTIPLE ZONE S. FARM OR LEASE NAME OTHER 2. NAME OF OPERATOR Gissler "B" REI Céived by Burnett Oil Co., Inc. 9. WELL NO. 3. ADDRESS OF OPERATOR O. C. D 1500 InterFirst Tower, For 1 1986 Workings Texas 10. FIELD AND POOL, OR WILDCAT 4. LOCATION OF WELL (Report location clearly and in accor-Square Lake (GB-SA) 760 1880 O. C. D. SEC., T., E., M., OR BLK. AND SURVEY OR AREA Unit Letter E, 660' FWL, FNL, Sec. 14-17 STESOF OFFICE At proposed prod. zone Same 14-17S-30E 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE 12. COUNTY OR PARISH 13. STATE 4 miles NE of Loco Hills, NM Eddy NM 15. DISTANCE FROM PROPOSED* 16. NO. OF ACRES IN LEASE 17. NO. OF ACRES ASSIGNED TO THIS WELL LOCATION TO NEAREST PROPERTY OR LEASE LINE, 660 120 (Also to nearest drlg. unit line, if any) 40 18. DISTANCE FROM PROPOSED LOCATIONS 19. PROPOSED DEPTH 20. ROTARY OR CABLE TOOLS TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. NA 3550 Rotary 21. ELEVATIONS (Show whether DF, RT, GR, etc.) 22. APPROX. DATE WORK WILL START* -3691' GR 3686 December 20, 1986 $\overline{23}$ PROPOSED CASING AND CEMENTING PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH QUANTITY OF CEMENT 12½" 9-5/8" OD 53.50 400' ±300 sks Cl. C (circulate) 7-7/8" 5½" OD 17 3550**'** ±500 sks Cl. C. If water flows encountered, cmtg. program will vary. A $12\frac{1}{4}$ " surface hole will be drilled to the Rustler anhydrite. 9-5/8" casing will be run and cemented to surface. After testing casing, a 7-7/8" OD hole will be drilled through the Jackson zone at ± 3550'. Open hole logs will be run (if no water flowing) and if commercial, $5\frac{1}{2}$ " casing will be run and cemented back to the base of the salt at ±1250'. BOP equipment will be double ram, tested to 3000 psi before drilling out underneath the surface pipe.

and if commercial, 5½" casing will be run and cemented back to the base of the salt at ±1250'. BOP equipment will be double ram, tested to 3000 psi before drilling out underneath the surface pipe.

IN ABOVE SPACE DESCRIBE PROFOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive sone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

TITLE Production Superintendent

APPROVAL DATE

APPROVAL DATE

DATE 11.36.56

