

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-028784-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keely-B Fed

9. WELL NO.

27

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson-7R-Q-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T-17-S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. PERMIT NO.

30-015-25713

15. ELEVATIONS (Show whether OF, BT, OR, etc.)

GL 3569', RKB 3578'

3570.3

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANE

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

3/28/87 Drilled 7-7/8" hole to TD of 4700'.

3/31/87 Ran 114 jts. 5-1/2" 17# K-55 csg. & set @ 4700'. Cmdt. w/1600 sk Class C cmt. w/ 10% Diacel D, 9#/sk salt & 800 sk Class C w/5#/sk salt. WOC 18 hrs. TOC @ 620' - temperature survey. PBTD 4660'.

4/6/87 Ran CNL-GR-CCL from 4660'-surface.

5/12/87 Install 3000 psi flange & BOP stack. Test to 3000 psi-OK.

5/13/87 Ran Gamma Ray/Collar Locator log from PBTD to 1500'. Perforated w/4" OD csg. guns w/ deep penetrating charges & spiral phasing as follows:

4320'-4356'	36'	36 holes-1 SPF	4503'-4505'	2'	4 holes-2 SPF
4411'-4419'	8'	16 holes-2 SPF	4509'-4513'	4'	8 holes-2 SPF
4427'-4434'	7'	14 holes-2 SPF	4620'-4630'	10'	20 holes-2 SPF
4486'-4498'	12'	12 holes-2 SPF		79'	110 holes

5/14/87 Set pkr. @ 4216'. Acidize perms w/7900 gals. of 15% NEFE NCL acid containing fines suspension agent & clay stabilizer. Swabbed acid wtr.

Temp. drop from report pending further activity.

ACCEPTED FOR RECORD

SJS

MAY 22 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Eng. Supervisor, Reservoir

DATE 5/19/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side