

Form approved.  
Budget Bureau No. 1004-0115  
Expires August 31, 1985

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

PERMIT IN TRIT  
(Other Institution  
version side)

ATR  
J. 10

3. LEASE DESIGNATION AND SERIAL NO.

LC-028784-C

6. IF INDIAN ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keely-C Fed

9. WELL NO.

60

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson-7R-Q-G-SA

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 13, T-17-S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. PERMIT NO.

30-015-25715

15. ELEVATIONS (Show whether OF, RT, OR, etc.)

GL 3640.6 (Unprepared)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Spud well - set surface csg. XX

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

2/19-20/87 Spud well. Drill 12-1/4" hole to 372'. Run 8 jts. 8-5/8" 24#, K-55 ST&C casing. Cement w/350 sk "C" w/2% CaCl. WOC 14.75 hrs. Slurry volume 462 cu ft. 6.3 gal. wtr./sk. Cement slurry temp. 90°. Est. min. formation temperature 70°. Est. cement strength 900-1000 psi.

ACCEPTED FOR RECORD

FEB 27 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNATURE

TITLE Eng. Supervisor, Reservoir

DATE 2/24/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side