

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OF COPIES REQUIRED
(Other Instructions on re-
quested forms)

EXCLUDED FORM NO.

NM-45223

5. LEASE DESIGNATION AND SERIAL NO.

NM-45223

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Empire Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Cave Grayburg-San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 6, T-17S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
TOM SCHNEIDER

3. ADDRESS OF OPERATOR
505 N. Big Spring St. Suite 204, Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

710' FNL, 1503' FWL of Section 6

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, OR, etc.)

3661 KB, 10' above GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROMISED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Please refer to attached schematic drawing of casing and perforations presently in well.

It is proposed to Plug and Abandon as follows:

NOTIFY BLM PRIOR TO COMMENCING PLUGGING.

1. Spot sufficient cement to provide at least 110' fill from 2365 to 2475' inside 5 1/2" casing, with at least 25 sacks cement. Tag plug.

2. Load hole with 9# per gallon mud.

3. Spot sufficient cement to provide 130' fill from 1755 to 1875' with at least 30 sacks. Tag plug.

3A. SPOT CEMENT PLUG FROM 265' - 165'. TAG PLUG.

4. Cement 50' surface plug in 5 1/2" casing and to surface in 8-5/8" casing.

4A. TOP 50' OF EVERY ANNULUS SHALL BE CEMENTED.

5. Weld or cement 4" pipe surface marker.

CEMENT TO BE USED: CLASS 'C' WITH 2 1/2% CaCl₂, MIXED WITH 6.3 GALLONS OF WATER PER SACK.

P&A ON 7/13/90.

18. I hereby certify that the foregoing is true and correct

SIGNED William F. Graffen TITLE Assistant Operations Manager DATE 1-7-91

William F. Graffen

(This space for Federal or State office use)

APPROVED BY William F. Graffen TITLE Assistant Operations Manager DATE 1-7-91

CONDITIONS OF APPROVAL, IF ANY:

Lighting, casing, and surface conditions are satisfactory.

*See Instructions on Reverse Side

RECEIVED

CARLOS
AREA

8 21 AM '90

Post ID-2
1-18-91
P&A