Form 3160-5 (November 1983) (Formerly 9-331)	DEPARTME'	ED STATES OF THE INTER		CATE!	Expires Augus	No. 1004-0135
	BUREAU Or	LAND MANAGEMEN	T			BA
(Do not use th	NDRY NOTICES Is form for proposals to d Use "APPLICATION F	AND REPORTS (rill or to deepen or plug look PERMIT—" for such	MAN TOWN THE THINK THE PROPERTY NO.	06 8	. IF INDIAN, ALLOTTI	E OR TRIBE NAME
OIL X WELL GAR	OTHER	/ (3	REPERT	C. D.	. UNIT AGREEMENT N	ANE
NAME OF OPERATOR	7		001 19 1981 ADDRE	3 . T	ARM OR LEASE NA	
Burnett 0il		÷ * •	Uni *	0	Gissler A	
ADDRESS OF OPERATO			2 1 M 3	9.	WELL NO.	1
801 Cherry,	Suite 1500, Fo	rt Worth, TX 76	5108	j	14	
See also space 17 be At surface	Report location clearly at low.)	id in accordance with any	State requirementa?	10). FIELD AND POOL, C	R WILDCAT
			0.30.3		Grayburg Ja	ickson = 1- P-G-
Unit Letter	A, 660' FNL, 7	80' FEL, Sec. 14	, T17S, R30E	11	SURVEY OR AREA	
. PERMIT NO.	15. EL	EVATIONS (Show whether DF,	RT, GR. etc.)	12	14-17S-30E	
	1	721' GR	•	12	Eddy	
l.	·					NM
			ature of Notice, Report,	or Othe	r Data	
	NOTICE OF INTENTION TO:		80	BSEQUENT	REPORT OF:	
TEST WATER SHUT-	PULL OR	ALTER CASING	WATER SHUT-OFF	X	REPAIRING V	PRI.I.
PRACTURE TREAT	MULTIPLE	COMPLETE	FRACTURE TREATMENT	y	ALTERING CA	
SHOOT OR ACIDIZE	ABANDON*		SHOOTING OR ACIDIZING		ABANDONME	I 1
REPAIR WELL (Other)	CHANGE F	LANS	(Other)			
DESCRIBE DRAWARES O	R COMPLETED OPERATIONS	Clearly state all pertinent	Completion or Re details, and give pertinent cons and measured and true v	combietion	nultiple completion Report and Log for	m.)
10/9/8/ 10/10 to 10/	survey. TOC 275 with 25 sks. Cl 3% CaCl ₂ . WOC. 5 sks. cement. NU BOP. GIH, to okay. Drilled 7 Ran 81 jts. new 500 gal. CW100, 12-3 RFC cement Ran GR/CNL/CBL. Perforated Mete 2963, 64 and 65 Acidized with 1 34,500# 20-40 s 12/87 Testing	Toc 125'. Cement Cementing complested 8-5/8" cas 7-7/8" hole to 3 250 sks. C1 C 6 250 sks. C1		id not /8". Ta mented C1 C, 4 hrs. r 30 m: 11:00 a @ 3553 5# sal /87. WO Teste 2917';	circulate. agged 285'. with 75 sks 3% CaCl ₂ . C in., okay. To a.m., 8/20/8 3' KB. Cement bt/sk., and color. Released ed casing to and Premier	Ran temp. Cemented . C1 C, irculate ested BOP, 7. POOH. ted with 260 sks. rig. 2000 psi.
I hereby certify that SIGNED (This space for Feder APPROVED BY	,	^	uction Superintend		DATE 10/16/	
CONDITIONS OF API	PROVAL, IF ANY:			i ^N ,	DATE	
		*See Instructions o		.##ED87	SJS AD, NEW ME)	(ICO