

OIL CONSERVATION DIVISION

P.O. BOX 2098
SANTA FE, NEW MEXICO 87501

RECEIVED

Form O-100
Revised 11/87

REGISTRATION	
DISTRIBUTION	
SANITARY	☒
FILE	☒
LAND OFFICE	☒
OPERATOR	☒

DEC 30 '87

O. C. D.

ARTESIA, OFFICE

V 734

SUNDRY NOTICES AND REPORTS ON WELLS

1. IF THE WELL IS BEING PLUGGED OR ABANDONED, THE PLUG MUST BE PLUGGED TO A DIFFERENT DEPTH THAN THE ORIGINAL PLUG. THE PLUG MUST BE PLUGGED TO A DIFFERENT DEPTH THAN THE ORIGINAL PLUG.

2. WELL ☒ OTHER ☐

Fred Pool Drilling Inc.

P.O. Box 1393, Roswell, N.M. 88201

UNIT LETTER P 660 FEET FROM THE South 660 FEET FROM THE East
TOWNSHIP 17S RANGE 30E

11. Elevation (show whether DE, RT, CR, etc.)

3601'

Cal-Mon State

Grayburg Jackson
Sr-Q-Gb-SA

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT ON:

TEMPORARY REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
FULL OR PARTIAL CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

PERMANENT WORK ☐
COMMENCE DRILLING, ETC. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ABANDONING CASINGS
XX PLUG AND ABANDONMENT

17. Describe Proposed Work, Test Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULES.

TD-3550 PA 12-28-87

12-23-87 Set CIBP @ 3125 ft. Spotted 30 sx cement plug from 3125' to 2725'
Spotted 25 sx cement plug from 2694' to 2394'
Spotted 25 sx cement plug from 1520' to 1220'
Spotted 25 sx cement plug from 400' to 100'
Filled 5 1/2' from the top with 10 sx cement to surface.
Pressured up to 300 PSI, pressure held.
Intend to install dry hole marker and clean location.

All cement used was Class C Neat.
No casing was recovered.

Post ID-2
11-4-88
P&A

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Santa Fe

TITLE Vice President

DATE 12-28-87

APPROVED BY Danell Moore

TITLE Geologist

DATE 1/5/89

CONDITIONS OF APPROVAL, IF ANY: