

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NEW OIL SUBMIT INSTRUCTIONS
(Other instructions on reverse side)
Mesa, NM 88210

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

| | | | | | | | | | | | |
|--|--|---|--|--|--------------------------------------|------------------------|---|-------------------|--|--|---|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 2. NAME OF OPERATOR Hondo Oil & Gas Company | 3. ADDRESS OF OPERATOR P. O. Box 2208, Roswell, NM 88202 | 4. LOCATION OF WELL (Report location clearly and in accordance with any State regulations. See also space 17 below.) At surface 1980' FSL & 660' FWL | 5. LEASE DESIGNATION AND SERIAL NO. LC-029426-B | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | 7. UNIT AGREEMENT NAME | 8. FARM OR LEASE NAME H. E. West "B" Federal | 9. WELL NO. 33 | 10. FIELD AND POOL, OR WILDCAT Grayburg Jackson | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 3-T17S-R31E | 12. COUNTY OR PARISH 13. STATE Eddy NM |
| 14. PERMIT NO. | 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3941' GR | | | | | | | | | | |

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded well @ 1:00 p.m. 8/2/88. Drilled 12 1/4" hole to 625'. Ran 15 jts. 8 5/8" 24# J-55 8rd casing and set @ 625'. Cemented w/300 sx. Class C w/2% CC. Circulated 20 sx. WOC 15 hrs. Drilled out shoe. Tested BOP to 500 psi for 30 min. - held okay. Drilled out w/7 7/8" bit 8/3/88.

Aug 5 11 11 AM '88
CARL
AREA

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

William D. Fulton

TITLE

Engineer

DATE

8/4/88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS