

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	✓
FILE	✓
COPIES	
FIELD OFFICE	✓
OPERATIONS	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-

SEP 07 '88

O. C. D.

ARTESIA, OFFICE

5a. Indicate Type of Lease
State ☒ For ☐

5. State Oil & Gas Lease No.
NM-5665

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-	7. Unit Agreement Name
2. Name of Operator Anadarko Petroleum Corporation ✓	8. Form or Lease Name Amoco State "36"
3. Address of Operator P. O. Drawer 130, Artesia, New Mexico 88211-0130	9. Well No. 1
4. Location of well UNIT LETTER: N 660 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 17S RANGE 30E NMPM.	10. Field and Pool, or Wildcat GB-J-SR-Q-GB-SA
15. Elevation (Show whether DF, RT, GR, etc.) 3591.5' G.L.	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Rigged up Rotary tools & spudded 12-1/4" hole @ 1600 hrs, 8/22/88 w/fresh wa mud. Drilled to 433' KB.
2. Ran 8-5/8", 24#, K-55, ST&C with guide shoe @ 433' KB & insert baffle float 392' KB. Western Co. cemented w/275 sx Class C w/2% CaCl & 1/4#/sx cellosea Plug down @ 0845 hrs 8/23/88, circ 43 sxs to pit.
3. WOC 19-1/2 hrs, nipples up & tested BOP to 1000# for 30 minutes, held ok.
4. Drilled 7-7/8" hole to TD of 3565' KB.
5. Schlumberger ran open hole logs.
6. Ran 84 jts (3548') 5-1/2", 15.5#, K-55, ST&C casing w/guide shoe @ 3560' KB & Float collar @ 3540' KB.
7. Western Co. cemented w/920 sxs Pacesetter Lite w/5#/sx gilsonite, 5#/sx salt & 1/4#/sx celloseal & tailed in w/250 sxs Class C w/8% Thixad, 3#/sx salt & 1/4#/sx celloseal. Plug down @ 1215 hrs 8/31/88. Circulated 200 sx to pit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James E. Duckles TITLE Area Supervisor DATE 09/06/88

APPROVED BY Mike Williams TITLE DATE SEP 7 1988

CONDITIONS OF APPROVAL, IF ANY: