

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OIL COM. COMMISSION
SUBMIT IN T Llicate
(Other instruat s on re
of the state, etc. slide)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

CISF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | |
|--|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 5. LEASE DESIGNATION AND SERIAL NO. LC-029435-B |
| 2. NAME OF OPERATOR Hondo Oil & Gas Company | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 3. ADDRESS OF OPERATOR P. O. Box 2208, Roswell, NM 88202 | 7. UNIT AGREEMENT NAME |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 1980' FEL | 8. FARM OR LEASE NAME J. L. Keel "B" |
| 14. PERMIT NO. | 9. WELL NO. 41 |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3884' GL | 10. FIELD AND POOL, OR WILDCAT Grayburg Jackson |
| | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 5-T17S-R31E |
| | 12. COUNTY OR PARISH 13. STATE Eddy NM |

RECEIVED

DEC 21 '88

O. C. D.

INTEREST, CHARGE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

11/17/88 Perforated 3172-3304' with 39 holes. Acidized 3172-3304' with 3000 gal. 15% NEFE acid. Swabbed well back.

11/18/88 Plugged well back to 3265' with sand.

11/19/88 Frac'd 3172-3264' (29 holes) with 40,000 gal. 30# cross-linked gel + 80,000# 20-40 sand. Flowed and swabbed well back.

APPROVED FOR RECORD

DEC 18 1988

ED

CASERAD NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ron Brown

TITLE Engineer

DATE 11/22/88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side