

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI  
(Other, Instructi  
verse 3160-5

CATE\*  
ON TE

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

dsf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Hondo Oil & Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 2208, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

1980' FSL & 860' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3857' GL

RECEIVED

DEC 12 '88

O. C. D.

WELLS, OFFICE

RECEIVED

5. LEASE DESIGNATION AND SERIAL NO.

LC-029426-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. AGREEMENT NAME

8. FARM OR LEASE NAME

H. E. West "B"

9. WELL NO.

35

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 9-T17S-R31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10/26/88 Perforated 3732-3791' with 18 shots.  
10/27/88 Acidized 3732-3791' with 3000 gal. 15% NEFE acid. Swabbed well back. Prep to squeeze.  
10/28/88 Set cement retainer @ 3721'. Pumped 127 sx. Class "C" Neat with 39 sx. in formation. Did hesitation squeeze to 2400 psi.  
10/29/88 Perforated 3457-3707' with 71 shots. Acidized 3457-3707' with 7000 gal. 15% NEFE acid. Flowed and swabbed well back.  
11/01/88 Reacidized 3457-3707' with 4000 gal. 15% NEFE acid. Frac'd 3457-3707' with 45,000 gal. 30# gelled water + 46,000# 20-40 sand. Flowed and swabbed well back.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE 11/14/88

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 7 1988

\*See Instructions on Reverse Side

SJS

CARLSBAD, NEW MEXICO