

RECEIVED

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

5. LEASE

LC-054908

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hudson Federal

9. WELL NO.

6

10. FIELD OR WILDCAT NAME

Gbr.-Jackson, 512-GB-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

18-17S-31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3699 GR

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

DEC 16 '88

2. NAME OF OPERATOR

Ray Westall

O. C. D.

3. ADDRESS OF OPERATOR

P.O. Box 4, Loco Hills, NM 88255

ARTESIA, OFFICE

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2310 FNL &amp; 990 FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐

(other) Spud &amp; casing

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-23-88 Spud 12 1/4" hole at 3:00 PM.

TD 373'. Set 373' of 8-5/8" 44# J-55 casing. Cemented with 275 sxs class "C" 2%. Circulated 20 sxs to pit. Plugged down at 11:15 p.m.

11-23-88. WOC 18 hrs. Pressure test to 800# held 30 min.

11-24-88 Drilled with 7-7/8" bit.

11-28-88 TD 3505'. Set 3505' of 5 1/2" 17# J-55 casing. Cemented with 1700sxs class "C" 2%. Circulated 286 sxs to pit. Plug down 12:57 PM 11-29-88 WOC 18 hrs. Pressure test to 1000# held 30 min. Released Rig.

ACCEPTED FOR RECORD

DEC 14 1988

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

CARLSBAD, NEW MEXICO

SIGNED

TITLE Geologist

DATE

12/1/88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: