				Form approved.	C15"
1160 5	יודרה כי	TATES # OIT	COS C ISSIC		
orm 3160-5 November 1983)	ONITED ST DEPARTMENT OF T	INICO	Other Instructions on	re 5, LEASE DESIGNATION	
Formerly 9-331)	DEPARTMENT OF	HE MILENION	い。 第20EIV	ED LC-029426-A	
	BUREAU OF LAND			6. IF INDIAN, ALLOTTES	OR TRIBE NAME
SUND	RY NOTICES AND	REPORTS ON \	VELLS		
(Do not use this for	rm for proposals to drill or to Use "APPLICATION FOR PER	n deepen or plug back to MIT" for such proposals	a different reservoir.	5 MM '88	
	)se AFFEICATION TON 12.		DEG	7. UNIT AGREEMENT NA	ME
OIL TO GAM	1		CARLL	_ job <u>E</u>	
NAME OF OPERATOR	OTHER		AREA H	S. FARM OR LEASE NAM	(R
		RECEIVED	l	H. E. West "	'A"
Hondo Oil & Gas	Company v			9. WELL NO.	
	Decreal 1 - NM - 882/	02 - 4		15	
P. O. BOX ZZUS,	Roswell, NM 8820 port location clearly and in acc	cordance with fir State	irements.*	10. FIELD AND POOL, O	
See also apace 17 below.) At surface				Grayburg Jackson 62 GJ	
660' FNL & 330' FEL		O. C. D.		11. SEC., T., R., M., OR BLE. AND SURVET OR AREA	
990. LMT % 220	LED	ARTESIA, OF	FICE		
		Allie		Sec.3-T17S-I	
4. PERMIT NO.	15. ELEVATION	S (Show whether Dr. RT, GR.	etc.)	12. COUNTY OR PARISH	13. STATE
		3990' GR		Eddy	NM
	CI I A . D	T. I. Jinata Matura	of Notice Percet o	- Other Data	
6.	Check Appropriate Bo	x to indicate tadinte			
ио.	TICE OF INTENTION TO:		8088	EQUENT REPORT OF:	[ <u>-</u>
TEST WATER SHUT-OFF	PULL OR ALTER C	CASING	WATER SHUT-OFF	X REPAIRING	WELL
FRACTURE TREAT	MULTIPLE COMPI	ETE	FRACTURE TREATMENT	ALTERING C	ASING
RHOOT OR ACIDIZE	ABANDON®		SHOOTING OR ACIDIZING	ABANDONME	HT*
REPAIR WELL	CHANGE PLANS		(Other)		
(Other)	COMPLETED OPERATIONS (Clear)		Completion or Reco	ults of multiple completion impletion Report and Log fo	rm.)
proposed work. II v	COMPLETED OPERATIONS (Clear) well is directionally drilled, gi				
nent to this work.) •	Spudded well @ 11 685'. Ran 17 jts Cemented with 450 WOC 11 1/2 hrs. Will drill out wi	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5	55 casing and s w/2% CC. Circu 00 psi for 1 hr	2 1/4" hole to set @ 685'. ulated 125 sx.	
	685'. Ran 17 jts Cemented with 450 WOC 11 1/2 hrs.	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5	55 casing and s w/2% CC. Circu 00 psi for 1 hr 1/26/88.	2 1/4" hole to set @ 685'. ulated 125 sx. c held okay.	
	685'. Ran 17 jts Cemented with 450 WOC 11 1/2 hrs.	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5	55 casing and sw/2% CC. Circumon psi for 1 hr. 1/26/88.	2 1/4" hole to set @ 685'. nlated 125 sx. c held okay.	
	685'. Ran 17 jts Cemented with 450 WOC 11 1/2 hrs.	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5	55 casing and sw/2% CC. Circumon psi for 1 hr. 1/26/88.	2 1/4" hole to set @ 685'. ulated 125 sx. c held okay.	
	685'. Ran 17 jts Cemented with 450 WOC 11 1/2 hrs.	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5	55 casing and sw/2% CC. Circumon psi for 1 hr. 1/26/88.	2 1/4" hole to set @ 685'. clated 125 sx. c held okay.  D FOR RECORD  C 1 3 1988	
	685'. Ran 17 jts Cemented with 450 WOC 11 1/2 hrs.	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5	w/2% CC. Circuion psi for 1 hr. 1/26/88.	2 1/4" hole to set @ 685'. nlated 125 sx. c held okay.	
11/22-24/88	685'. Ran 17 jts Cemented with 450 WOC 11 1/2 hrs. Will drill out wi	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5 ith 7 7/8" bit 1	w/2% CC. Circuion psi for 1 hr. 1/26/88.	2 1/4" hole to set @ 685'. clated 125 sx. c held okay.  C 1 3 1988	
11/22-24/88	685'. Ran 17 jts Cemented with 450 WOC 11 1/2 hrs.	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5 ith 7 7/8" bit 1	55 casing and sw/2% CC. Circulon psi for 1 hr. 1/26/88.  ACCEPTE  CARLSBA	2 1/4" hole to set @ 685'. ilated 125 sx. c held okay.  C 1 3 1988  C 1 3 1988  D, NEW MEMICO	
11/22-24/88	685'. Ran 17 jts Cemented with 450 WOC 11 1/2 hrs. Will drill out wi	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5 ith 7 7/8" bit 1	55 casing and sw/2% CC. Circulon psi for 1 hr. 1/26/88.  ACCEPTE  CARLSBA	2 1/4" hole to set @ 685'. clated 125 sx. c held okay.  C 1 3 1988	
11/22-24/88	Cemented with 450 WOC 11 1/2 hrs. Will drill out wi	s. 8 5/8" 24# J- ) sx. Class "C" Tested BOP to 5 ith 7 7/8" bit 1	55 casing and sw/2% CC. Circulon psi for 1 hr. 1/26/88.  ACCEPTE  CARLSBA	2 1/4" hole to set @ 685'. ilated 125 sx. c held okay.  C 1 3 1988  C 1 3 1988  D, NEW MEMICO	