

## ATTACHMENT VI

WELL NAME	LOCATION	SPUD DATE	COMPLETION DATE	TYPE OF WELL	DEPTH/PBTD TOC	COMPLETION RECORD
H. E. West "A" #17	660' FSL & 660' FEL Sec. 4-17S-31E	12/12/89	1/6/90	Producing Oil	TD 3954' PBTD 3906'	8 5/8" @ 575' w/350 sx cmt. Circ. to surface. 5 1/2" @ 3948' w/1150 sx cmt. Circ. to surface. Completed as a producer from the Grayburg San Andres formation thru perfs 3273'-3839'.
H. E. West "A" #22	1345' FSL & 35' FEL Sec. 4-17S-31E	2/3/93	3/31/93	Producing Oil	TD 5022' PBTD 3560'	13 3/8" @ 604' w/350 sx cmt. 8 5/8" @ 1815' w/750 sx cmt. 5 1/2" @ 5022' w/1222 sx cmt. Completed in Grayburg San Andres through perfs 3278'-3522'.
H. E. West "A" #23	140' FSL & 35' FEL Sec. 4-17S-31E	3/1/93	9/8/93	Producing Oil	TD 4308' PBTD 4287'	13 3/8" @ 595' w/250 sx. Circ. to surface. 5 1/2" @ 4308' w/1600 sx cmt. Circ. to surface. Completed as an oil producer in the Grayburg San Andres from perfs 3259'-3530' (48 holes).
H. E. West "B" #55	1972' FSL & 2078 FWL Sec. 3-17S-31E	2/21/93	5/6/93	Injection	TD 4300' PBTD 4265'	13 3/8" @ 575' w/300 sx. Circ'd cmt. 8 5/8" @ 1768' w/850 sx. Circ'd cmt. 5 1/2" @ 4266' w/1000 sx. Circ'd cmt. Completed as an oil producer thru perfs 4142'-4206' (92 holes) from the Grayburg San Andres. Well converted to injection thru Grayburg San Andres perfs 3314'-4206'.
H. E. West "B" #50	50' FSL & 1400 FWL Sec. 3-17S-31E	3/4/93	7/21/93	Producing Oil	TD 4356' PBTD 4285'	13 3/8" @ 576' w/250 sx. Circ to surface. 5 1/2" @ 4356' w/1900 sx. Circ. to surface. Completed in the Grayburg San Andres as a producer thru perfs 3300'-4052' (286 holes).
H. E. West "B" #44	720' FSL & 1980' FWL Sec. 3-17S-31E	2/9/93	3/21/93	Producing Oil	TD 4400' PBTD 3925'	8 5/8" @ 580' w/450 sx. 5 1/2" @ 4400' w/100 sx Completed as an oil producer thru perfs 3294'-3844' in the Grayburg San Andres.
H. E. West "B" #38	2085' FNL & 1980' FWL Sec. 10-17S-31E		12/85	Producing Oil	TD 3960' PBTD 3930'	8 5/8" @ 596' w/400 sx. Circ to surface. 5 1/2" @ 3960' w/1300 sx. Circ to surface. Completed in the Grayburg San Andres as a producer from perfs 3364'-3562', 3587'-3727', and 3757'-3910'.

## ATTACHMENT VI

H. E. West "B" #36	1980' FNL & 660' FEL Sec. 9-17S-31E	10/15/88	11/10/88	Producing Oil	TD 3883' PBTD 3861'	8 5/8" @ 541' w/400 sx. Circ to surface. 5 1/2" @ 3883' w/1300 sx. Circ. to surface. Completed as a producer from the Grayburg San Andres. Perfs 3199'-3821' (166 holes). Acidized w/6000 gals acid. Frac'd w/ 23,000 gals 30# gelled water + 15,000# 20/40 sand. 8 5/8" @ 625' w/300 sx cmt, circ to surface. 5 1/2" @ 4057' w/1300 sx cmt. TOC 2262' (CBL). Completed as producer in Grayburg San Andres through perf 3367'-3994'.
H. E. West "B" #33	1980' FSL & 660' FWL Sec. 3-17S-31E	3/2/88	8/20/88	Producing Oil	TD 4057' PBTD 4011'	8 5/8" @ 625' w/300 sx cmt, circ to surface. 5 1/2" @ 4057' w/1300 sx cmt. TOC 2262' (CBL). Completed as producer in Grayburg San Andres through perf 3367'-3994'.
H. E. West "B" #28	660' FNL & 660' FEL Sec. 9-17S-31E		12/63	Injection	TD 3850' PBTD 3850'	8 5/8" @ 550' w/240 sx. 5 1/2" @ 3850' w/300 sx. TOC @ 1600' (calc). Completed in the Grayburg San Andres as an injector thru perfs 3289'-3849'. Added new perfs from 3270'-3823'.
H. E. West "B" #19	660' FNL & 1980' FWL Sec. 10-17S-31E	2/28/64	3/13/64 Deepened in 8/89	Injection	TD 3955' PBTD 3954'	Surface: 10 3/4" @ 785' w/100 sx. Intermediate: 5 1/2" @ 3501' w/100 sx. Liner: 4" from 3323' to 3953' w/ 65 sx. Perforated: 3373'-3941' (39 shots). Acidized w/13,000 gals acid. Frac'd w/25,000 gals x-linked gel and 9200# 20/40 sand.
H. E. West "B" #18	660' FSL & 1980' FEL Sec. 3-17S-31E	10/22/58	12/16/58 Recompleted 7/18/89	Injection	TD 3996' PBTD 3996'	10 3/4" @ 797' w/100 sx 5 1/2" @ 3725' w/100 sx. Drilled deeper and recompleted as water injection well thru perfs 3386'-3705' and open hole 3725'-3996'.
H. E. West "B" #13	1980' FNL & 660' FWL Sec. 10-17S-31E		10/57	Injection	TD 3900' PBTD 3720' CIBP	10 3/4" @ 739' w/100 sx. 7" @ 3525' w/100 sx. 5" liner set from 3094'-3897' w/150 sx cmt. Completed in the Grayburg San Andres as a producer from perforations 3318'-26' and 3356'-74'. The well was deepened to 3900' and a 5" liner set. The well was perf'd 3737'-3864', 3568'-3696' and 3312'-3559'. A cast iron bridge plug was set @ 3720' and the well converted to water injection.

ATTACHMENT VI

H. E. West "B" #1	660' FNL & 1980' FEL Sec. 10-17S-31E	NA	9/29/89	Producing Oil	TD 5515' PBTD 3950'	8 5/8" @ 810' w/400 sx cmt. 4 1/2" @ 5515' w/850 sx cmt. Well completed as a producer from Grayburg San Andres thru perforations 3380'-3754' & 3800'-3935'.
H. E. West "B" #47	890' FNL & 1980' FEL Sec. 9-17S-31E	12/2/89	12/11/89	Producing Oil	TD 3922' PBTD 3905'	8 5/8" @ 539' w/350 sx. Circ. 5 1/2" @ 3922' w/1400 sx. TOC @ 875' from CBL. Completed as a producer from Grayburg San Andres thru perfs 3265'-3859'.
H. E. West "B" #49	1305' FSL & 1305' FWL Sec. 3-17S-31E	4/5/93	8/29/93	Producing	TD 4350' PBTD 4276'	8 5/8" @ 618' w/300 sx. Circ. 5 1/2" @ 4350' w/1300 sx. Circ. Completed as a producer from the Grayburg San Andres thru perfs 3314'-3532' (50 holes). Additional perfs 3360'-3532' (280 holes).