

ATTACHMENT VI

<u>WELL NAME</u>	<u>LOCATION</u>	<u>SPUD DATE</u>	<u>COMPLETION DATE</u>	<u>TYPE OF WELL</u>	<u>DEPTH/PBTD</u>	<u>COMPLETION RECORD</u>
H. E. West "B" #28	660' FNL & 660' FEL Sec. 9-17S-31E	11/27/63	12/29/63	Injection	TD 3850' PBTD 3850'	8 5/8" @ 550' w/240 sx cmt. 5 1/2" @ 3850' w/300 sx cmt. TOC @ 1600' (calc.) Well completed in the Grayburg San Andres as an injector thru perforations 3289'-3849'. Added new perfs from 3270'-3823'.
H. E. West "B" #40	560' FNL & 660' FWL Sec. 10-17S-31E	12/22/88	2/2/89	Producing Oil	TD 4021' PBTD 3956'	8 5/8" @ 603' w/350 sx. Circ to surface. 5 1/2" @ 4021' w/1250 sx. Circ to surface. Completed in the Grayburg San Andres as a producer from perfs 3345'-3941' (170 holes). Acidized w/11,000 gals acid. Frac'd w/36,000 glas x-linked gelled water & 76,000# 20/40 sand.
H. E. West "B" #54	75' FNL & 1370' FEL Sec. 9-17S-31E	3/10/93	5/11/93	Producing Oil	TD 4310' PBTD 4256'	8 5/8" @ 618' w/300 sx cmt. Circ to surface. 5 1/2" @ 4310' w/1850 sx. Circ to surface. Completed as a Greyburg San Andres producer through perfs 4031'-4132' (63 holes). Additional perfs 3230'-3520', 3766'-3871' and 4048'-4250'. Acidized w/3000 gals 15% NEFE. Acid frac'd w/ 15,000 gals gelled Super x emulsified acid.
H. E. West "A" #23	140' FSL & 35' FEL Sec. 4-17S-31E	3/1/93	9/8/93	Producing Oil	TD 4308' PBTD 4287'	13 3/8" @ 595' w/250 sx. Circ to surface. 5 1/2" @ 4308' w/1600 sx. Circ to surface. Completed as a producer in the Grayburg San Andres from perforations 3259'-3530' (48 holes).
H. E. West "A" #14	720' FSL & 1980' FEL Sec. 4-17S-31E	11/2/88	12/2/88	Producing Oil (Proposed injector)	TD 3955' PBTD 3828'	8 5/8" @ 542' cemented w/350 sx. Circ to surface. 5 1/2" @ 3935' w/1900 sx cmt. Circ to surface. Completed in the Grayburg San Andres as a producer from 3214'-3467', 3492'-3678', and 3709'-3863'.