

MARBOB ENERGY CO. CORPORATION
 Foster Eddy #10
 Sec. 17-T17S-R31E
 Eddy County, New Mexico
Perforations & Treatment

2882-2888	3767
2940-2946	3782
3170-3180	3799
3388	3802
3396	3838
3402	3842
3419	3845
3422	4200
3430	4206
3432	4214
3435	4218
3442	4226
3451	4232
3484	4240
3493	4247
3498	4450
3506	4458
3513	4462
3676	4466
3686	4474
3698	4500-4509
3703	
3718	
3727	
3762	

12/9/91 Perfed csg from 2882-4509'

12/10/91 Acd perfs 4500-4509 w/500 gals. 15% NE ac.

12/11/91 Acd perfs 4450-74 & 4200-47 w/500 gals. 15% NE ac, acd perfs 3676-3845 w/2000 gals. 15% NE ac.

12/12/91 Acd perfs 3484-3513 w/750 gals. 15% NE ac, acd perfs 3388-3513 w/750 gals. 15% NE ac.

12/13/91 Acd perfs 3171-79 w/400 gals. 15% NE ac, acd perfs 2882-2940 w/600 gals. 15% NE ac.

12/14/91 Frac perfs 4500-09 w/500 bbls. gel wtr & 147 sx 20/40 & 152 sx 12/20 sand.

12/16/91 Frac perfs 4200-4474 w/40,000 gals. 40# gel wtr and 222 sx 20/40 & 442 sx 12/20 sand.

12/18/91 Acd perfs 3676-3845 w/54,000 gals. heated 40# gel wtr and 32,000 gals. heated 20% ac.

12/23/91 Sqzd perfs 3484-3513 w/46 sx Class C w/2% CC.

12/30/91 Acd perfs 3388-3451 w/27,000 gals. heated 40# gel wtr and 16,000 gals. heated 20% NE ac, flushed w/5000 gals. 15% NE ac and 4000 gals. frsh wtr.

12/31/91 Frac perfs 3171-79 w/20,000 gals. 40# gel wtr and 114 sx 20/40 sand.

1/2/92 Frac perfs 2882-2948 w/40,000 gals. 40# gel wtr and 222 sx 20/40 & 442 sx 12/20 sand.