	-	NM.	OK Cons. #		٠.	1	
		1 J.V.	i yy wranc	1 4 KEAL 1985	•	dsi	
Form 3160-5 (November 1994)	UNITED STATE	INTERIOR	tesia, NM	35 10	FORM APPROVED OMB No. 1004-0135 Expires July 31, 1996		
SUNDE	BUREAU OF LAND MANA		15 234567 85	5. Lease S LC	erial No. 029339A		
Do not use tl	his form for proposals to ell. Use Form 3160-3 (AP	drill or to re-e	nter an 🖌	6. If India	n, Allottee or Tribe Nam	e	
SUBMIT IN TR	IPLICATE - Other instr	uctions on rev	erseside	び び 子 て. If Unit o	or CA/Agreement, Name	and/or No.	
1. Type of Well Q Oil Well Gas Well	Cher	<u> </u>	ARTED ESIA	57 8. Well Na	ame and No.		
2. Name of Operator BURNETT OIL CO.,	TNC			JA 9. API We	CKSON A #16		
3a. Address BURNETT PLAZA- SUITE 15003b. Phone No. (include area code)801 CHERRY STREET UNIT#9 FORT WORTH, TX76102-6881817/332-5108				30	30-015-26968 10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec			017/332-310		DAR LAKE YESO	rea	
	70' FEL, SEC 13.T17S,F			· ·	or Parish, State dy County, N.M.		
12. CHECK AF	PROPRIATE BOX(ES) T	O INDICATE N	ATURE OF NOTIC	E, REPORT, OI	R OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent	Acidize	Deepen	_	(Start/Resume)	Water Shut-Off		
Subsequent Report	Alter Casing	U Fracture Treat	_		Well Integrity		
	Casing Repair Change Plans	New Construct		e y Abandon	Other		
Ginal Abandonment Notice	Convert to Injection	Plug Back	Water Disp	•			
determined that the site is ready 11/26/01 Notified Don H 11/27 MI Computalog, r 5 1/2" csg off slips, run f casing. Water flowing to 11/28 GIH 1183' 2 3/8" c GIH w/wireline to top o tapered mill, set cement Class C neat cement. Stir out of cement to surface. 12/06 Installed dry hole 12/17 Preparing to remo WILL FILE A FINAL AI	Early w/BLM for start of I un gauge ring to 2800', set ree point, found free @ 11 pit, had I&W haul water open ended tbg, MI BJ, put f cement plug @ 1062'. Sta retainer @ 430'. MO Com ng out of retainer & pump MO BJ. Cut off 8 5/8" cas marker and removed flow we caliche from location a BANDONEMENT NOTIC	P&A. MIRU Ke t CIBP @ 2790', o 40'. Shot 5 1/2"o off. SWIFN. mped 30 sks Cla rt in hole w/8 5 putalog, GIH w 115 sks Class C sing. No BLM o vline. nd restore locat	y Rig, POOH w/rod lump 35' cement or off @ 1133'. MI csg c ass C cement w/ 2% i/8" retainer- hit so /stinger & tbg, stin i neat cement to sur n location during a ion for reseeding.	Approved Liability un ds & t SUM29 SE top of plug, N rrew & POOH w 6 CaCl. POOH w mething. Drill o g into retainer of face. POOH w/	as to plugging of the inder bond is retained what ion is complete ID wellhead. Pull w/27 JT's 51/2". w/tbg, wait 11/2 but rubber w/85/ & pump 35 sks / tbg & stinger & to APPROV	e well bore i until st. hrs. '8" ost op	
 I hereby certify that the foregoin Name (Printed/Typed) 	-	Ti			JAN 4 A	102	
Signature	STERLING RANDOLPH	D	PETROLEUM E		LES BABYA		
(Iterling)	lan Migh		17/18	1200	PETROLEUM ENG	21.XLUIX	
Approved by	THIS SPACE F	OR FEDERAL	DR STATE OFFICE		ate		
			Title		ait	<u></u>	
Condition certify 1 Accepted for record which w FEB	5 2002	does not warrant in the subject lea					
fraudule only		ngly and willfully diction.	to make to any departme	ent or agency of the	United States any false	, fictitious or	
Instruc			٠				