

H.E. WEST "B" 55
ATTACHMENT 1
OF FORM #3160-4

4/24/93 PERFORATED
Slaughter perf 4202'-4150' (92 holes) in acid. Allow acid to soak on
perf over night.

4/25/93 Acidize Slaughter perf 4206'-4142' w/2000 gal 15% NEFE acid. Dropped
3 salt blocks. Max press 1800#, Avg press 1450#, AIR 2 BPM, ISIP
1400#.

4/25/93 Swab Slaughter perf 4206'-4142'. Final swab 23% oilcut. Fluid level
holding 2300' FS.

4/26/93 Swab Slaughter perf 4206'-4142'. 1st Run 20% oilcut. Final run 20%
oilcut. Fluid level holding 3200' FS.

5/5/93 Frac Slaughter perf 4142'-4206' w/2000 gal 15% HCL acid & 10,000 gal
Super-X Emulsified acid. Max 1480#, Avg IR 3 BPM, Min 0#, ISIP 1450#.

5/6/93 Swab Slaughter perf 4206'-4142' 12 Runs 6% oilcut. Fluid level
holding 2300' FS.

WELL NAME AND NUMBER H. E. West "B" No. 55
LOCATION 1972' FSL & 2078' FWL, Section 3, T17S, R31E, Eddy County, NM
OPERATOR Socorro Petroleum
DRILLING CONTRACTOR United Drilling, Inc.

The undersigned hereby certifies that he is an authorized representative of the drilling contractor who drilled the above described well and had conducted deviation tests and obtained the following results:

<u>Degrees @ Depth</u>	<u>Degrees @ Depth</u>	<u>Degrees @ Depth</u>
<u>1/4° 500'</u>	<u>3/4° 3036'</u>	<u> </u>
<u>3/4° 1044'</u>	<u>3/4° 3223'</u>	<u> </u>
<u>1° 1508'</u>	<u>3/4° 3408'</u>	<u> </u>
<u>1° 1768'</u>	<u>3/4° 3595'</u>	<u> </u>
<u>1° 2009'</u>	<u>3/4° 3813'</u>	<u> </u>
<u>3/4° 2228'</u>	<u>1/2° 3999'</u>	<u> </u>
<u>3/4° 2414'</u>	<u>1/2° 4217'</u>	<u> </u>
<u>3/4° 2819'</u>	<u> </u>	<u> </u>

Drilling Contractor United Drilling, Inc.
By: *D. M. Gibbs*
Title: Business Manager

Subscribed and sworn to before me this 4th day of March,
1993.

Karna Laskewsky
Notary Public

My Commission Expires: 9-25-95 *Chaves* *N.M.*
County State